



---

## Symbols

- \* wildcard character [7](#)
- .gz extension [44](#)
- .nsc file [39](#)
- .pac files [37](#)

---

## A

- AAA accounting
  - activating on Content Engine [5](#)
  - command accounting [2](#)
  - displaying configuration of [8](#)
  - EXEC shell accounting [2](#)
  - overview of [2](#)
  - statistics for [8](#)
  - system accounting [2](#)
  - with TACACS+ [2](#)
- AAA-based management systems [16](#)
- accelerated WCCP support [34](#)
- access control
  - authentication and authorization
    - of administrative login [1](#)
    - of content requests [2](#)
  - IP ACLs [2](#)
  - RealProxy [8](#)
- access control lists. *See* IP ACLs
- access control services, deploying [15](#)
- accessing
  - Content Engine CLI [50](#)
  - Content Engine GUI [55](#)
- access lists, group name-based
  - disabling [53](#)
  - for group authorization [47](#)
- access lists, WCCP
  - configuring [20](#)
  - displaying [20](#)
- access-lists 300 command [46](#)
- access-lists 300 deny groupname any command [49](#)
- access lists enable command [46](#)
- ACLs. *See* IP ACLs
- ACNS software CLI
  - accessing [51](#)
  - command modes [8](#)
- ACNS solution
  - components of [1](#)
  - overview of [1](#)
- Active Directory groups
  - description of [33](#)
  - group searches [49](#)
- administrative login accounts
  - default account [19](#)
  - managing [3](#)
  - types of [3](#)
- administrative login authentication and authorization
  - default [3](#)
  - for standalone Content Engines [2](#)
  - local database
    - description of [6](#)
    - enabling and disabling [16](#)
  - overview of [2](#)
- RADIUS
  - enabling and disabling [17](#)
  - overview of [6](#)
- TACACS+
  - enabling and disabling [18](#)

- overview of 7
  - administrative login authentication failover 4
  - administrative users
    - AAA accounting for 2
    - login accounts for 3
  - administrator levels
    - normal-level users 3
    - superusers 3
  - advanced caching features 14
  - alarm information
    - for all alarms 15
    - for critical alarms 15
    - for major alarms 15
    - for minor alarms 15
  - alarms
    - displaying
      - counts of 17
      - history of 15
      - list of 15
      - status of 17
    - overload of 13
  - alarm traps
    - configuring 14
    - disabling 14
    - enabling 14
    - generating 14
    - list of 14
  - Apache CLF transaction logging format 36
  - Apache-style transaction logging 36
  - Application and Content Networking System. *See* ACNS
  - AUP
    - configuration of 54
    - description of 54
  - authenticated HTTP cache settings 12
  - authentication
    - content authentication 1
    - end-to-end authentication 13
    - HTTP request authentication 13
    - traffic bypass 2
    - WMT proxy authentication 10
  - authentication, authorization, and accounting. *See* AAA
  - authentication cache
    - configuring 12
    - size adjustments 12
  - authentication command 3, 15
  - authentication configuration local command 17
  - authentication configuration radius command 15
  - authentication configuration tacacs command 19
  - authentication databases
    - standalone Content Engines and 2
    - types of 2
  - authentication fail-over command 4
  - authentication local login command 15
  - authentication login local command 17
  - authentication login radius command 15
  - authentication login tacacs command 19
  - authentication servers
    - LDAP servers 5
    - NTLM servers 5
    - RADIUS servers 5
  - authorization
    - administrative login authorization 1
    - content authorization 11
- 
- B**
  - bandwidth
    - and network resources 11
    - interface, configuring 11
  - bandwidth configuration 11
    - advanced configuration 26
    - incoming and outgoing 23
    - subnet-based bandwidth control 24, 12
  - bandwidth control
    - and content preloading 11
  - binary objects, description of 2
  - BIOS upgrades 24
  - block.html

- customized blocking message [17](#)
- browser configuration
  - for direct proxy routing [5](#)
- bypass
  - authentication traffic [2](#)
  - static [7](#)
- bypass auth-traffic command [5](#)
- bypass gateway command [5](#)
- bypass lists
  - displaying summary of [3](#)
  - static entries in [7](#)
- bypass load command [8](#)
- bypass options
  - disabling for URL filtering [12](#)
- bypass timer command [4](#)

## C

- cache
  - expiration date [10](#)
- cache freshness
  - for FTP cache [40, 43](#)
  - for HTTP cache [9](#)
- cache hits
  - description of [2](#)
  - refresh [13](#)
- cache misses
  - description of [2](#)
  - no-proxy action [13](#)
  - using upstream proxy [13](#)
- caching
  - CTE HTTP objects [7](#)
  - description of [2](#)
  - disabling for certain clients [24](#)
  - hierarchy [10](#)
  - HTTP and [2](#)
  - network protocols and [2](#)
  - nontransparent caching
    - proxy-style [13](#)
  - terminology [8](#)
  - TFTP and [2](#)
  - transparent caching [14](#)
- caching and streaming services
  - with direct proxy routing [13](#)
  - with transparent redirection [14](#)
- caching services
  - configuring with Setup utility [11](#)
  - conventional caching services [2](#)
  - RTSP streaming and caching services [5](#)
  - WMT streaming and caching services [5](#)
- calendar
  - setting [4](#)
- caveats
  - pattern list group type [35](#)
- CDP. *See* Cisco Discovery Protocol
- cfs
  - function of [26, 9](#)
- characters
  - special [34](#)
- chunked transfer coding, description of [7](#)
- Cisco Discovery Protocol
  - enabling [2](#)
  - purpose of [2](#)
- Cisco IP/TV, description of [11](#)
- Cisco Streaming Engine, description of [10](#)
- CiscoWorks2000 [26](#)
- clear ip access-list counter [24](#)
- clear ip wccp command [1](#)
  - for WCCP Version 2 [34](#)
- clear statistics rule command [33](#)
- clear statistics rule rtsp command [33](#)
- clear statistics tacacs command [8](#)
- clear websense command [27](#)
- clear wmt incoming command [45](#)
- clear wmt outgoing command [46](#)
- clear wmt stream-id command [46](#)
- CLF, description of [36](#)
- CLI

- accessing 51
- command modes 8
- EXEC mode 9
- global configuration mode 9
- HTTPS server configuration mode 9
- interface configuration mode 9
- keyboard shortcuts 10
- logging in to 50
- online help
  - accessing 10
  - usage guidelines 10
- clients
  - description of 3
  - support of 12
- clock
  - clearing and setting 4
  - daylight saving and local time, setting 4
  - displaying standard timezones 4
  - UTC offset, setting 4
- clock summertime command 4
- command accounting
  - activating on Content Engine 2
  - overview of 4
- command-line interface. *See* CLI
- configuring
  - AAA accounting 1
  - administrative login authentication and authorization 8
  - alarm traps 14
  - authentication and authorization
    - for administrative users 8
    - for content requests 1
  - bandwidth 11
  - content preloading 2
  - conventional caching services 2
  - custom-web-cache service
    - on Content Engine 20
  - disk space allocation 25, 9
  - dns-cache service
    - on Content Engines 62
  - FTP connection settings 36
  - FTP native caching service
    - on Content Engines 55
  - HTTP request authentication 16
  - https-cache service
    - on Content Engines 27
    - on WCCP routers 29
  - ICAP services 4
  - interface bandwidth 11
  - IP ACLs 10
  - IP spoofing 10
  - native ftp caching service
    - on WCCP routers 29
  - passwords 24
  - playserver 10
  - RADIUS authentication 10
  - reverse-proxy service
    - on Content Engines 23
    - on WCCP routers 33
  - Rules Template 1
  - standard web-cache service
    - on Content Engines 18
    - on WCCP routers 27
  - static bypass 7
  - transaction logging 1
  - URL filtering 1
  - user-defined WCCP services 15
- content
  - classifications 5
  - on-demand 5
  - preloaded 5
  - pre-positioned 6
  - types of 5
- content authentication
  - of HTTP requests 13
  - overview of 2
- content authorization
  - of LDAP users 47
  - of NTLM users 48

- overview of 2
- content distribution, types of 5
- Content Engine
  - ACNS software GUI
    - logging out 57
    - main components of 53
  - automatic reload 18
  - bandwidth configuration 11
  - configuring for IP spoofing 10
  - configuring for WCCP 11
  - mounting to a NAS device 13
  - rebooting 24
  - removing or replacing 24
  - security 35
- Content Engine administrators
  - normal-level users 3
  - superusers 3
- Content Engine CLI
  - command modes 8
  - logging in to 50
  - logging out of 52
  - online help 10
- Content Engine clusters
  - configuring ICP clients for 5
  - configuring ICP servers for 5
- Content Engine GUI
  - disabling access to 54
  - enabling access to 54
  - exiting 57
  - feature tabs 2
  - logging in to 55
  - logging out from 57
  - managing administrative login accounts 8
  - Reporting tab and subtabs 7
  - System tab and subtabs 6
  - WCCP tab and subtabs 2
- content preloading
  - configuring 2
  - creating filter for 5
  - creating preload URL list file 3
  - default start time 5
  - enabling 2
  - forcing 5
  - NTLM preloading support 2
  - preloading authenticated content 3
  - resuming after aborting 11
  - scheduling 5
  - setting DSCP 6
  - setting Type of Service (ToS) 6
  - specifying maximum bandwidth for 5
  - stopping operation 11
  - viewing statistics for 8
  - viewing statistics for current preload 8
  - viewing status of current preload 7
- conventional caching services
  - configuring 2
- conventions, documentation 26
- copy running-config command 13
- CTE HTTP objects, caching 7
- custom blocking messages
  - in URL filtering 12
- custom format transaction logging 36
- custom messages
  - for FTP proxy responses 19
  - for HTTP requests 14
- custom web cache service
  - configuring
    - on Content Engines 20
    - on WCCP routers 32

---

## D

- daylight savings time
  - setting 4
- daylight saving time
  - setting 4
- debug ip wccp events command 42
- debug ip wccp packets command

- for WCCP Version 1 42
  - debug wmt error command 55
  - debug wmt trace command 55
  - default administrative login account 19
  - default user account 3
  - directing requests back to proxy server 7
  - direct proxy routing
    - caching services with 13
    - configuring
      - browsers for 5
      - media players for 5
    - forward proxy caching and 3
    - streaming services with 13
    - supported services for 13
  - disabling
    - access to Content Engine GUI 54
    - caching for certain clients 24
    - local authentication and authorization 16
    - persistent connections 68
    - RADIUS authentication 20
    - RADIUS authentication and authorization 17
    - RealProxy caching 30
    - SNMP agents 10
    - TACACS+ authentication and authorization 18
    - transparent caching services 14
    - WCCP flow redirection 17
  - disk add command 9
  - disk config command 11
  - disk config sysfs command 10
  - disk configuration, displaying 12
  - disk configuration settings
    - configuring
      - through CLI 14
      - through Setup utility 14
  - disk delete-partitions command 11
  - disk drives
    - error handling thresholds
      - description of 18
      - specifying 18
    - manually unmarking 19
    - removing partitions from 11
  - disk error-handling reload command 18
  - disk error-handling threshold command 18
  - disk mark command 19
  - disk partitions, removing 11
  - disks
    - configuring
      - space allocation 25, 9
      - sysfs space 11
    - NFS and CIFS storage 18, 13
    - storage types 9
  - disk unuse command
    - disk drives
      - unusing 12
  - dns-cache service
    - configuring
      - on routers 28
      - on standalone Content Engines 62
  - DNS caching service
    - configuring WCCP transparent interception for 64
    - disabling 67
    - overview of 63
  - dns use-original-server command 64
  - documentation conventions 26
  - DSCP
    - rule action 12
    - Rules Template 6
  - dynamic traffic bypass 5
- 
- E**
- ecn enable command 3
  - EIM
    - through content authentication 2
    - through group-based authorization 11
    - through URL filtering with SmartFilter 39
  - employee Internet management. *See* EIM
  - enabling 2

- dynamic authentication bypass [4](#)
  - local authentication and authorization [16](#)
  - persistent connections [68](#)
  - RADIUS authentication and authorization [17](#)
  - SNMP agent [6](#)
  - transparent error handling [5](#)
  - WCCP [12](#)
  - WCCP flow redirection [17](#)
  - WCCP on routers [23](#)
  - enabling and disabling
    - NTLM allow domain lists [44](#)
  - error logging, WMT [11](#)
  - EtherChannel configuration [2](#)
  - Ethernet MAC address mapping [17](#)
  - EXEC CLI mode [9](#)
  - EXEC shell accounting
    - activating on Content Engine [2](#)
    - overview of [3](#)
  - extended IP ACLs
    - configuration examples [22](#)
    - configuring [10](#)
    - supported conditions [14](#)
    - supported keywords [12](#)
    - TCP keywords [12](#)
    - typical uses of [5](#)
  - Extended Squid-style transaction logging [35](#)
  - Extended Squid transaction log format [36](#)
  - external FTP server
    - exporting transaction logs to [43](#)
    - permanent error from [45](#)
- 
- F**
- failover
    - for administrative login authentication [4](#)
  - Fast Cache
    - configuring on Content Engines [31](#)
  - Fast Start
    - configuring on Content Engines [29](#)
  - Fibre Channel interface
    - configuring [9](#)
  - file system types
    - description (table) [9](#)
  - filtering services
    - deploying [15](#)
    - URL filtering [11](#)
  - flow protection
    - WCCP [9](#)
  - forwarding
    - HTTP, HTTPS, and FTP proxy-style requests [7](#)
  - forward proxy caching, overview of [3](#)
  - FTP
    - configuring connection settings [38](#)
    - description of [2](#)
    - FTP native caching
      - overview of [54](#)
  - FTP caching
    - nontransparent FTP native caching [42](#)
    - transparent FTP native caching [54](#)
  - ftp min-ttl command [10](#)
  - FTP native caching
    - nontransparent caching
      - caching [42](#)
    - overview of [54](#)
    - transparent caching
      - configuring [55](#)
      - displaying statistics for [46, 58](#)
  - ftp native caching service
    - configuring on standalone Content Engines [55](#)
  - ftp-native custom-message command [19](#)
  - ftp-native proxy active-mode command [55](#)
  - FTP native proxy servers
    - displaying configuration of [57](#)
  - FTP objects
    - configuring object freshness [4](#)
  - FTP-over\_HTTP proxy servers
    - displaying configuration of [41](#)
    - displaying statistics for [41](#)

FTP-over-HTTP caching  
   configuring 39

ftp-over-http object max-size command 40

ftp-over-http proxy active-mode enable command 40

ftp-over-http proxy anonymous-pswd command 40

FTP-over-HTTP proxy caching  
   specifying incoming ports 39, 43

ftp-over-http proxy incoming command 39, 43

ftp-over-http proxy outgoing command 40

ftp-over-http proxy outgoing monitor command 8

ftp-over-http reval-each-request all command 40

ftp proxy outgoing host command 4

FTP requests  
   native  
     configuring access lists for 42, 19  
     configuring nontransparent FTP native caching 42  
     configuring proxy authentication for nontransparent requests 55  
     configuring transparent FTP native caching 54  
     creating custom messages for 19

ftp-server gw proto command 60

FTP servers  
   exporting transaction logs to 43

FTP statistics, displaying 28

---

## G

generic routing encapsulation. *See* GRE encapsulation

global configuration CLI mode 9

global exclusion from proxy forwarding 7

GLOP addresses 17

GRE encapsulation 5

group authorization  
   Active Directory group searches 49  
   methods of 2  
   of LDAP users 47

GUI. *See* Content Engine GUI

gui-server command 54

gzip format

to compress archived log files 44

---

## H

healing mode, configuration of 70

hierarchical caching 10

hostname command 14

HTTP 14  
   authenticated cache settings 12  
   cache freshness settings 9  
   outgoing proxy exclusion 5  
   proxy failover 2  
   status codes of 37

http age-multiplier command 10, 11

http append x-forwarded-for-header command 15, 11

http authenticate-strip-ntlm command 8

HTTP authentication cache  
   configuring 12  
   displaying configuration of 16

HTTP authentication cache, configuring 12

http authentication cache timeout command 17

http authentication command 12

http cache-authenticated ntlm command 2, 3

http cache-chunk-encoded enable command 7

http cache-cookies command 10

HTTP caching  
   configuring  
     nontransparent forward proxy caching 8  
     reverse proxy caching 23  
     transparent HTTP forward proxy caching 17  
   types of 7

http cluster command 71

http cluster heal-port command 71

http cluster http-port command 71

http cluster max-delay command 71

http cluster misses command 72

http custom-error-page command 16

http l4 switch enable command 5

http max-ttl command 11

- http min-ttl command [10,11](#)
  - http monitor url command [5](#)
  - HTTP objects
    - configuring object freshness [4](#)
  - HTTP proxy caching
    - configuring
      - through Content Engine CLI [7](#)
      - through Setup utility [29](#)
  - http proxy incoming command [14](#)
  - http proxy outgoing host command [3](#)
  - http proxy outgoing monitor command [8](#)
  - http proxy outgoing origin-server command [2](#)
  - HTTP request authentication [44](#)
    - configuring [16](#)
    - hierarchical caching
      - in proxy server mode [14](#)
    - logging failures of [50](#)
    - methods of [2](#)
    - overview of [13](#)
    - transaction logging [18](#)
    - transparent mode [15](#)
  - HTTP requests
    - creating custom message pages for [14](#)
  - http reval-each-request all command [11](#)
  - http reval-each-request command [11](#)
  - HTTP reverse proxy caching
    - configuring
      - through Content Engine CLI [14](#)
      - through Setup utility [14](#)
  - HTTPS
    - description of [3](#)
    - Rules Template with [2](#)
    - server configuration CLI mode [9](#)
    - statistics, displaying [28](#)
  - https-cache service
    - configuring
      - on sContent Engines [27](#)
      - on WCCP routers [29](#)
  - HTTPS caching
    - configuration of [24](#)
    - SSL termination and [24](#)
  - https certgroup command [33](#)
  - https command [32](#)
  - HTTPS errors, displaying [28](#)
  - HTTPS outgoing proxy servers
    - configuring [27](#)
    - displaying current state of [27](#)
  - https proxy command [26](#)
  - HTTPS proxy commands [26](#)
  - https proxy outgoing host command [34,4](#)
  - https proxy outgoing monitor command [8](#)
  - HTTPS statistics, displaying [28](#)
  - HTTP statistics, displaying [28](#)
  - HTTP transparent caching
    - configuring
      - through Content Engine CLI [14](#)
      - through Setup utility [14](#)
- 
- IANA [16,11](#)
  - ICAP [5](#)
    - approved vendors [3](#)
    - configuring
      - Content Engine settings [5](#)
      - server [8](#)
      - services [7](#)
    - maximum file size supported [4](#)
    - overview of [1](#)
  - icap append-x-headers command [5](#)
  - icap apply command [4](#)
  - icap bypass streaming-media command [6](#)
  - icap logging enable command [4](#)
  - icap service command [7](#)
  - ICAP services
    - configuring [4](#)
    - description of [2](#)
  - icap service server command [8](#)

- ICP
  - client settings [73](#)
  - server settings [74](#)
- icp client command [73](#)
- ICP clients
  - configuring [5](#)
- icp server command [74](#)
- ICP server configuration [74](#)
- IFP
  - role of [19](#)
- inetd enable tftp command [59, 60](#)
- interface bandwidth [11](#)
- interface command [19, 2](#)
- interface configuration CLI mode [9](#)
- interface-level DHCP [7](#)
- Internet Assigned Numbers Authority. *See* IANA
- Internet Cache Protocol. *See* ICP
- Internet Content Adaption Protocol. *See* ICAP
- Internet Filtering Protocol. *See* IFP
- Internet service provider. *See* ISP
- ip access-group command [16](#)
- ip access-list command [3](#)
- ip access-list extended command [5](#)
- ip access-list standard command [5](#)
- IP ACLs
  - activating [6](#)
  - activating on an interface [16](#)
  - applying to interface [17](#)
  - clearing counter [24](#)
  - clearing IP ACL counter [24](#)
  - configuration modes [9](#)
  - defining [6](#)
  - deleting [23](#)
  - description of [2](#)
  - extended configuration mode
    - accessing [5](#)
    - description of [5](#)
  - extended IP ACLs
    - typical uses of [5](#)
  - naming guidelines [9](#)
  - overview of
  - standard configuration mode
    - accessing [5](#)
    - description of [5](#)
  - standard IP ACLs
    - typical uses of [5](#)
  - types of [4](#)
  - viewing configuration of [23](#)
- ip address dhcp command [17](#)
- IP addresses
  - multiple IP addresses on a single interface [9](#)
- ip default-gateway command [14](#)
- ip default-gateway command (global configuration) [5](#)
- ip domain-name command [14](#)
- IP multicasting
  - and insecure services [16](#)
  - copying files between server and client [16](#)
  - Ethernet MAC address mapping [17](#)
  - fundamentals [16](#)
  - GLOP addresses [17](#)
  - Layer 2 multicast address considerations [17](#)
  - limited scope addresses [16](#)
  - Protocol Independent Multicast. *See* PIM
  - source-specific multicast addresses [16](#)
- ip name-server command [64](#)
- ip name-servers command [14](#)
- ip route-cache same-interface command [24](#)
- ip route command [5](#)
- IP spoofing
  - configuration of [10](#)
  - examples of [12](#)
  - WCCP and [10](#)
- ip wccp command [26](#)
- ip wccp password command
  - WCCP Version 2 commands
    - ip wccp password [23](#)
- ip wccp redirect-list command [26](#)
- ip wccp redirect out command [25](#)

ip web-cache redirect command [1, 26](#)

## K

keystroke combinations, CLI [10](#)

## L

launching

Setup utility [19](#)

Layer 2

multicast address [17](#)

redirection [8](#)

Layer 4 switches

forward proxy caching and [8](#)

reverse proxy caching and [13](#)

LDAP

security options [23](#)

LDAP acceptable use policy

configuration of [54](#)

description of [54](#)

LDAP Active Directory [33](#)

LDAP databases

contents of [28](#)

entries in [29](#)

querying [33](#)

structure of [28](#)

LDAP directory service

description of [28](#)

directory entries [28](#)

LDAP memory cache

disabling [35](#)

specifying the maximum TTL for an object [53](#)

specifying the size of [35](#)

LDAP nested static groups

description of [31](#)

searching for user account information [37](#)

LDAP password expiration

configuration of [54](#)

description of [54](#)

ldap server command [23](#)

ldap server enable command

LDAP authentication

for HTTP requests [23](#)

ldap server group command [24](#)

ldap server password-expiry command [54](#)

ldap server policy-redirect attribute command [54](#)

ldap server policy-redirect enable command [54](#)

ldap server policy-redirect redirect-url command [54](#)

LDAP servers

configuring for Content Engine [5](#)

types of [22](#)

ldap server version 3 command [33](#)

LDAP Version 3

enabling [33](#)

less command [9](#)

license keys

RealProxy

restoring factory defaults [29](#)

uninstalling [31](#)

limited scope addresses [16](#)

list of

nontransparent mode services [13](#)

supported caching and streaming services

with transparent redirection [14](#)

WCCP features and services [10](#)

WCCP services [3](#)

live content

description of [6](#)

live splitting

description of [10](#)

load-balance command [4](#)

load balancing [5](#)

load shedding [5](#)

log files

exporting [43](#)

restarting export of [45](#)

- logging command [22](#)
- logging console priority command [23](#)
- logging disk command [24](#)
- logging host command [25](#)
- logging host hostname command [25](#)
- logging in to
  - Content Engine GUI [55](#)
- logging on
  - to Content Engine
    - using GUI [50](#)
    - using SSH [52](#)
    - using Telnet [50](#)
- logging out
  - of Content Engine CLI [52](#)
  - of Content Engine GUI [57](#)
- login authentication
  - local method [15](#)

---

## M

- MAC address mapping [17](#)
- MAC address table [17](#)
- mapping of RealProxy error level to syslog priority level [26](#)
- media file system. *See* mediaafs
- mediaafs
  - configuring
    - through the Setup utility [25](#)
  - function of [9](#)
- media player configuration
  - for direct proxy routing [5](#)
- media player configuring
  - for direct proxy routing [5](#)
- menu options
  - Setup utility [14](#)
- MIBs
  - supported [5](#)
- monitoring
  - with ACNS software alarms [11](#)

- with SNMP [2](#)
  - with the Cisco Discovery Protocol [2](#)
- monitoring URLs [5](#)
- mounting to NAS devices [18, 13](#)
- multicast
  - WMT, logging [48](#)
- multicast address
  - unusable assignments [12](#)
- multicasting
  - See also* IP multicasting
- multicast stations
  - defining [40](#)
  - description of [40](#)
  - starting and stopping [42](#)
- multiple IP addresses
  - configuring on a single interfacesconfiguring [9](#)
- multiple router support [8](#)

---

## N

- N2H2 URL filtering [12](#)
- NAS devices
  - mounting to [18, 13](#)
- native ftp caching service
  - configuring
    - on WCCP routers [29](#)
- near-miss
  - definition [70](#)
- network connectivity
  - testing [10](#)
- network interfaces
  - configuring [2](#)
- network settings
  - configuring
    - through CLI [14, 19](#)
- no authentication login local enable command [17](#)
- no authentication login radius enable command [18](#)
- no auto-register enable command [22](#)
- Node Health Manager

- description of 11
  - Node Manager
    - description of 13
  - no disk error-handling reload command 18
  - no dns-cache size command 67
  - no ntlm basic-auth enable command 45
  - no ntlm server ad-group-search mem-cache command 35
  - nontransparent caching
    - SSL tunneling and 6
  - nontransparent FTP native caching
    - description of 42
  - nontransparent mode
    - forward proxy caching 3
  - nontransparent mode services
    - list of 13
  - nontransparent requests
    - description of 4
  - no pre-load enable command 11
  - no radius-server enable command
    - RADIUS authentication
      - disabling 20
  - no rtsp proxy media-real enable command 30, 31
  - no snmp-server command 10
  - no snmp-server enable traps command 11
  - no transaction-logs export enable command 47
  - no transaction-logs logging enable command 48
  - no transaction-logs logging facility command 48
  - no transaction-logs logging host command 48
  - no wccp version command 14
  - no wmt enable command 31, 13
  - no wmt license-key command 13
  - NTLM
    - description of 3
    - end-to-end authentication
      - object caching 9
      - pass-through service 9
    - NTLMv1
      - re-enabling 6
    - NTLMv2
      - enabling 6
    - ntlm allow-domain enable command 44
    - NTLM allow domain lists
      - enabling and disabling 44
    - ntlm basic-auth enable command 45
    - NTLM preloading support 2
    - ntlm server ad-group-search command 52
    - ntlm server ad-group-search mem-cache command 52
    - ntlm server ad-group-search mem-cache max-ttl command 53
    - ntlm server ad-group-search mem-cache size command 53
    - ntlm server command 41
    - ntlm server enable command 49
    - ntlm server host command 48
    - NTLM servers
      - configuring for Content Engine 5
    - ntlm version 2 command 6
- 
- ## O
- on-demand content
    - description of 5
  - origin web servers
    - description of 3
  - outgoing FTP-over-HTTP proxy servers
    - monitoring 8
  - outgoing FTP proxy servers
    - configuration of 8
    - configuring 4
    - designating primary server 3
  - outgoing HTTP proxy servers 8
    - designating primary server 3
    - monitoring 7
  - outgoing HTTPS proxy servers
    - configuration of 8
    - configuring 4
    - designating primary server 4
    - monitoring 8

outgoing proxy servers

- primary outgoing HTTP proxy server [3](#)
- primary outgoing HTTPS proxy server [4](#)

overload bypass

- configuring [8](#)
- description of [2](#)
- overview of [8](#)

## P

packet flow

- diagram [2](#)

packet marking [12](#)

PAP

- password authentication [12](#)

Password Authentication Protocol. *See* PAP

password configuration [24](#)

pattern list group type

- caveats [35](#)

pattern lists

- adding pattern to [29](#)
- associating an action with [30](#)
- configuring [28](#)

persistent connections

- configuring [5](#)
- disabling [68](#)
- enabling [68](#)
- purpose of [68](#)

PIM [16](#)

ping command [10](#)

PNA

- support of [3](#)

port lists

- WCCP services and [12](#)

pre-load concurrent-requests command [4](#)

pre-load depth-level-default command [4](#)

pre-load dscp command [6](#)

preloaded content [5](#)

pre-load enable command [4](#)

pre-load fetch domain command [5](#)

pre-load force command [5](#)

preloading authenticated content [3](#)

preloading content

- bandwidth control [11](#)
- support for ToS and DSCP [6](#)

pre-load max-bandwidth command [5](#)

pre-load no-fetch suffix command [5](#)

pre-load schedule command [5](#)

pre-load schedule every-week command [6](#)

pre-load traverse-other-domains command [5](#)

preload URL list file

- creating [3](#)
- description of [3](#)

pre-load url-list-file command [3,5](#)

pre-positioned content, description of [6](#)

primary interface

- changing to a different interface [8](#)

primary outgoing proxy servers

- designating for FTP-over-HTTP [4](#)
- designating for HTTP [3](#)
- designating for HTTPS-over-HTTP [27,4](#)

Progressive Networks Audio. *See* PNA

Protocol-Independent Multicast. *See* PIM

proxy authentication

- WMT caching proxy [10](#)

proxy authentications

- for nontransparent FTP native requests [55](#)
- types of [10](#)

proxy-auto-config download command [38](#)

proxy-auto-config enable command [38](#)

proxy failover [2](#)

proxy forwarding

- excluding items [6](#)

proxying services

- overview of [7](#)

proxy protocols

- parameters [6](#)

proxy-protocols command [6](#)

proxy-protocols outgoing-proxy exclude command [34](#)  
 proxy-protocols transparent command [34](#)  
 proxy-protocols transparent default-server command [34](#)  
 proxy-protocols transparent original-proxy command [26](#)  
 proxy-protocols transparent reset command [34](#)  
 proxy servers  
   description of [7](#)  
 proxy-style requests, description of [4](#)

---

## Q

QuickTime, description of [10](#)

---

## R

### RADIUS

  URL filtering [12](#)

### RADIUS authentication

  configuring [10](#)  
   overview [6](#)

### RADIUS key

  specifying on Content Engine [10](#)

radius-server command [16](#)

radius-server host command [11](#)

radius-server key command [11](#)

radius-server retransmit command [11](#)

### RADIUS servers

  as authentication servers [10](#)  
   authentication settings [10](#)  
   configuring for Content Engine [5](#)  
   redirect [13](#)

radius-server timeout command [11](#)

Range requests [67](#)

### RealMedia

  description of [10](#)

### Real Media caching

  configuring  
     through Setup utility [15](#)

RealMedia players, description of [13](#)

### Real Media proxy caching

  configuring  
     through Content Engine CLI [15](#)  
     through Setup utility [15](#)

### Real Media transparent caching

  configuring  
     through Content Engine CLI [15](#)

RealPlayer [46](#)

### RealProxy

  and access control [8](#)  
   disabling [13](#)  
   disabling RealProxy caching [30](#)  
   enabling [13](#)  
   error codes [26](#)  
   features and benefits [3](#)  
   license keys  
     restoring factory defaults [29](#)  
   licenses  
     accepting [13](#)  
     evaluation [13](#)  
     permanent [13](#)  
     specifying [13](#)  
   restarting [30](#)  
   restoring default configuration [29](#)

### RealProxy caching

  disabling [30](#)

### RealProxy license key

  installing [13](#)  
   uninstalling [31](#)

### RealProxy statistics

  displaying [31](#)

RealSystem administrator page [22](#)

RealTime Streaming Protocol. *See* RTSP

rebooting Content Engine [24](#)

redirected HTTP traffic [20](#)

### registering router

  to a multicast address [24](#)

### regular expressions

- special characters [34](#)
- reloading Content Engine
  - automatic reload option [18](#)
- removing
  - Content Engines [24](#)
  - disk partitions [11](#)
- replacing Content Engines [24](#)
- restarting export of log files [45](#)
- retransmit count
  - for RADIUS server authentication [10](#)
  - for TACACS+ server authentication [12](#)
- reverse proxy caching
  - Layer 4 CSS switch
    - configuration process [14](#)
  - through Layer 4 switching [13](#)
  - through WCCP-enabled routers [10](#)
- reverse proxy service
  - configuring on Content Engine [2](#)
- reverse-proxy service
  - configuring
    - on Content Engines [23](#)
    - on routers [33](#)
    - on WCCP routers [33](#)
- router lists
  - defining for WCCP services [12](#)
- RTSP
  - description of [3](#)
  - overview of [3](#)
  - Rules Template [2](#)
  - support of [3](#)
- RTSP gateway
  - overview [10](#)
  - purpose of [14](#)
  - related commands [16](#)
- rtsp ip-address command [16](#)
- rtsp l4-switch enable command [18](#)
- rtsp proxy media-real accept-license-agreement command [13](#)
- rtsp proxy media-real enable command [13](#)
- RealMedia proxy caching
  - enabling [20](#)
- rtsp proxy media-real evaluate command [13](#)
- rtsp real-proxy default-configuration command [14](#)
- rtsp real-proxy restore factory-default command [29](#)
- RTSP streaming and caching services
  - description of [5](#)
  - list of [5](#)
- rule action no-persistent-connection command [68](#)
- rule actions
  - list of [11](#)
  - order of execution [20](#)
  - overview of [5](#)
  - supported action and pattern combinations [17](#)
- rule command [20](#)
- rule no-auth domain command [17](#)
- rules processing
  - configuring [23](#)
  - deleting rules [31](#)
  - enabling [23](#)
  - performance guidelines [35](#)
- Rules Template
  - actions
    - associating with a pattern list [30](#)
    - list of [11](#)
    - order of execution [20](#)
  - configuring [1](#)
  - deleting rules [31](#)
  - DSCP [6](#)
  - enabling rule processing [23](#)
  - order of executing actions [20](#)
  - pattern lists
    - adding patterns to [29](#)
    - configuring [28](#)
  - patterns
    - list of [7](#)
    - order of execution [21](#)
    - setting ToS or DSCP [12](#)
    - supported rule patterns [7](#)

## S

### sanitizing transaction logs

- enabling [42](#)
- purpose of [42](#)

### satellite connections

- and TCP [6](#)

### scheduling

- content preloading [5](#)

### secret keys

- RADIUS [10](#)
- TACACS+ [12](#)

### Secure Shell. *See* SSH

### security on Content Engine [35](#)

### setting password [24](#)

### setup command [19](#)

### Setup utility

#### configuring

- HTTP proxy caching [29](#)
- HTTP reverse proxy caching [14](#)
- HTTP transparent caching [14](#)
- Real Media proxy caching [15](#)
- Real Media transparent caching [15](#)
- WMT proxy caching [15](#)
- WMT transparent caching [15](#)

#### disk configuration [14](#)

#### keys and arrows [15](#)

#### launching [19](#)

#### manually invoking [12](#)

#### menu options [14](#)

#### usage guidelines [12](#)

### sfadmin console [39](#)

### show alarm command [15](#)

### show alarm critical command [15](#)

### show alarm detail command [15](#)

### show alarm major command [15](#)

### show alarm minor command [15](#)

### show alarms history command [15](#)

### show alarms history detail support command [16](#)

### show alarms status command [17](#)

### show authentication user command

- administrative authentication
- displaying configuration of [19](#)

### show bypass summary command [3](#)

### show clock command [17](#)

### show clock standard-timezones details command [5](#)

### show clock standard-timezones region command [5](#)

### show clock standard-timezones zones command [5](#)

### show clock standard-timezones all command [4](#)

### show disks command [10](#)

### show disks details command [12](#)

### show ftp-native command [57](#)

### show ftp-over-http command [41](#)

### show ftp-over-http statistics command [41](#)

### show ftp proxy command [8](#)

### show http authentication command [16](#)

### show http proxy command [2, 8](#)

### show https proxy command [27, 8](#)

### show http ttl command [12](#)

### show inventory command [2](#)

### show ip interface command

- for WCCP Version 1 [39, 41](#)

### show ip wccp web-caches command

- for WCCP Version 1 [42](#)

### show logging command

#### syslog hosts

- displaying configuration for [22](#)

### show pre-load command [7](#)

### show rtsp proxy media-real license-agreement command [13](#)

### show running-config command [4](#)

### show snmp group command [10](#)

### show statistics bandwidth advanced command [26](#)

### show statistics ftp-native command [46, 58](#)

### show statistics http command [8](#)

### show statistics http miss-reason command [3](#)

### show statistics http performance command [2](#)

### show statistics http requests command [48](#)

- show statistics http savings command [2](#)
- show statistics pre-load command [8](#)
- show statistics rtsp proxy command [31](#)
- show statistics rtsp proxy media-real requests command
  - RealMedia statistics
    - displaying [30](#)
- show statistics url-filter http websense command [38](#)
- show statistics wccp gre command [22](#)
- show statistics wmt requests command [47](#)
- show statistics wmt streamstat command [47](#)
- show tech-support command [2](#)
- show transaction-log command [51](#)
- show wccp command [41](#)
  - for WCCP Version 1 [42](#)
  - for WCCP Version 2 [17](#)
- show wccp content-engines command [17](#)
- show wccp flows ftp-native command [9](#)
- show wccp gre command [49](#)
- show wccp masks command [37](#)
- show wccp masks ftp-native command [57](#)
- show wccp services command [16](#)
- show wmt diagnostics command [11](#)
- show wmt http allow extension command [21](#)
- show wmt license-agreement command [17](#)
- shutting down WCCP [17](#)
- Simple Network Management Protocol. *See* SNMP
- SmartFilter software
  - description of [39](#)
  - URL filtering [39](#)
- SMIL, description of [6](#)
- SNMP
  - defining SNMPv3 user accounts [8](#)
  - enabling SNMP agent [6](#)
  - monitoring with [2](#)
  - security models and security levels [4](#)
  - supported MIBs [5](#)
  - versions supported [4](#)
- SNMP agents, disabling [10](#)
- snmp-server access-list command [18](#)
- snmp-server community command [6](#)
- snmp-server community string command [10](#)
- snmp-server enable traps alarm clear-critical
  - command [14](#)
- snmp-server enable traps alarm clear-major command [14](#)
- snmp-server enable traps alarm clear-minor command [14](#)
- snmp-server enable traps alarm raise-critical
  - command [14](#)
- snmp-server enable traps alarm raise-major command [14](#)
- snmp-server enable traps alarm raise-minor command [14](#)
- snmp-server enable traps command [9, 14](#)
- snmp-server group command [9](#)
- snmp-server host command [9](#)
- SNMP traps
  - configuring [8](#)
  - disabling [11](#)
  - enabling [9](#)
- source-specific multicast address [16](#)
- special characters
  - in regular expressions [34](#)
- Squid transaction log format [36](#)
- SSH, support of [52](#)
- sshd command [52](#)
- ssh-key-generate command [52](#)
- SSL tunneling
  - nontransparent caching and [6](#)
- standard IP ACLs
  - configuring [10](#)
  - supported conditions [14](#)
  - typical uses of [5](#)
- standard timezones, displaying [4](#)
- standard web-cache service
  - configuring
    - on standalone Content Engines [18](#)
    - on WCCP routers [27](#)
- standby groups, interfaces of [5](#)
- starting and stopping
  - WMT multicast stations [41](#)
- startup dialog

- for configuring network settings [21](#)
  - static bypass
    - configuring [7](#)
    - examples [7](#)
  - statistics
    - general CFS disk [7](#)
    - performance [7](#)
    - TCP requests [7](#)
    - WMT streaming [7](#)
  - statistics for [8](#)
  - statistics wmt requests command [47](#)
  - streaming media
    - sample deployment [12](#)
    - supported protocols [12,3](#)
  - streaming media caching
    - description of [11](#)
  - streaming media files
    - delivery of [11](#)
    - description of [11](#)
  - streaming media players
    - Cisco IP/TV Viewer [13](#)
    - QuickTime [13](#)
    - RealMedia players [13](#)
  - streaming media protocols
    - RTSP [3](#)
  - streaming media services
    - configuring [11](#)
    - licenses for [10](#)
  - streaming media solutions
    - Cisco IP/TV [11](#)
    - Cisco Streaming Engine [10](#)
    - QuickTime [10](#)
    - RealMedia [10](#)
    - WMT [9](#)
  - streaming services
    - supported with
      - direct proxy routing [13](#)
      - transparent redirection [14](#)
  - stream splitting [39](#)
  - superuser
    - AAA accounting for [2](#)
    - description of [19](#)
  - sysfs
    - configuring disk space for [11](#)
    - purpose of [26,9](#)
  - syslog
    - priority level mapping to RealProxy error codes [27,26](#)
  - syslog hosts, configuring [24](#)
  - system accounting
    - activating on Content Engine [2](#)
    - overview of [3](#)
  - system logging
    - configuring [25](#)
      - to console [23](#)
      - to disk [24](#)
      - to remote hosts [24](#)
- 
- ## T
- TACACS [18](#)
  - TACACS+
    - AAA accounting and [2](#)
  - TACACS+ authentication
    - configuring for HTTP requests [20](#)
    - password authentication method [12](#)
  - TACACS+ authentication and authorization
    - enabling [18](#)
    - overview of [7](#)
  - TACACS+ enable password attribute [8](#)
  - TACACS+ key
    - specifying on Content Engine [12](#)
  - TACACS+ servers
    - specifying as authentication servers [12](#)
  - tacacs key command [12](#)
  - tacacs password command [13](#)
  - tacacs retransmit command [13](#)
  - tacacs server command [12](#)
  - tacacs timeout command [13](#)

- TCP
  - configuring parameters using Content Engine GUI [2](#)
    - over satellite extensions [6](#)
  - tcp client-mss command [3](#)
  - tcp client-receive-buffer command [3](#)
  - tcp client-rw-timeout command [3](#)
  - tcp client-satellite command [3](#)
  - tcp client-send-buffer command [3](#)
  - tcp cwnd-base command [3](#)
  - tcp increase-xmit-timer-value command [3](#)
  - tcp init-ss-threshold command [3](#)
  - tcp keepalive-probe-cnt command [3](#)
  - tcp keepalive-probe-interval command [3](#)
  - tcp keepalive-timeout command [3](#)
  - TCP memory
    - configuring limits for [4](#)
  - tcp memory-limit command [4](#)
  - TCP memory limits
    - default settings for [5](#)
  - tcp server-mss command [3](#)
  - tcp server-receive-buffer command [3](#)
  - tcp server-rw-timeout command [3](#)
  - tcp server-satellite command [3](#)
  - tcp server-send-buffer command [2](#)
  - telnet command [10](#)
  - testing
    - connectivity of URLs
      - for FTP-over-HTTP [8](#)
      - for HTTP [7](#)
  - test-url comand
    - troubleshooting
      - with the HTTP CLI client [7](#)
  - test-url ftp test-URL command [8](#)
  - test-url http test-URL command [7](#)
  - text conventions [26](#)
  - text objects
    - description of [2](#)
- TFTP
  - caching and [2](#)
    - description of [2](#)
  - TFTP gateway
    - configuring [60](#)
    - enabling [58, 59](#)
  - TFTP server
    - configuring [60](#)
    - enabling [58, 59](#)
  - tftp-server access-list command [61](#)
  - tftp-server dir command [59, 60](#)
  - thresholds
    - disk error handling [18](#)
  - timeout intervals
    - for RADIUS server authentication [10](#)
    - for TACACS+ server authentication [12](#)
  - timeout of a nonresponsive host [10](#)
  - time zone setting [4](#)
  - token strings [36](#)
  - ToS
    - Rules Template [12](#)
    - setting [12](#)
  - traceroute command [11](#)
  - transaction logging
    - and NTLM authentication [42](#)
    - Apache-style format [36](#)
    - custom format [36](#)
    - default settings [32](#)
    - Extended Squid-style format [35](#)
    - for HTTP request authentication [18](#)
    - formats [36](#)
    - specifying facility [49](#)
    - WMT [10, 48](#)
  - transaction-log logging entry-type all command [50](#)
  - transaction logs
    - archiving of [46](#)
    - displaying configuration of [51](#)
    - exporting [43](#)
    - including domain name in [49](#)
    - including username in [49](#)
    - sanitizing [42](#)

- sending to remote syslog hosts [49](#)
  - specifying entry type [50](#)
- transaction-logs archive command [46](#)
- transaction-logs export sftp-server command [44](#)
- transaction-logs format apache command [36](#)
- transaction-logs format custom command [36](#)
- transaction-logs format extended-squid command [35](#)
- transaction-logs logging enable command [50](#)
- transaction-logs logging entry-type command [50](#)
- transaction-logs logging facility command [49](#)
- transaction-logs logging host command [49](#)
- transaction-logs log-windows-domain command [42, 49](#)
- transaction-logs sanitize command [18](#)
- transaction-logs sanitized command [43](#)
- transaction moitoring
  - disabling export feature [47](#)
- transparent caching
  - IP spoofing and [10](#)
  - outgoing proxy exclusion and [5](#)
- transparent caching services
  - disabling [14](#)
  - enabling [11](#)
- transparent forward proxy caching
  - overview of [6](#)
  - WCCP-enabled router and [9](#)
- transparently received proxy-style requests [6](#)
- transparent mode
  - advanced caching features [14](#)
  - hierarchical caching in [15](#)
  - supported caching services in [14](#)
- transparent modelist of
  - supported services [14](#)
- transparent redirection
  - streaming services with [14](#)
  - supported caching services [14](#)
  - supported services for [14](#)
- troubleshooting
  - in real time [9](#)
  - URL performance [5](#)

- with debug tool [4](#)
  - with HTTP CLI client [7](#)
  - with HTTP statistics tools [2](#)
  - with log viewing tool [9](#)
  - with ping [10](#)
  - with Telnet client [10](#)
  - with traceroute [10](#)
  - with WMT diagnostic tools [11](#)

## TTL

- maximum TTL setting [10](#)
- minimum TTL setting [10](#)

Type of Service. *See* ToS

type-of-service enable command [3](#)

type-tail working.log follow command [9](#)

---

## U

UDI compliance [2](#)

## UDP

- purpose of [3](#)

unusable multicast address assignments [12](#)

updating the calendar [4](#)

url-filter http bad-sites-deny enable command [14](#)

url-filter http bad-sites-deny file command [14](#)

url-filter http custom-message command [16](#)

url-filter http good-sites-allow enable command [16, 14](#)

url-filter http good-sites-allow file command [16, 14](#)

url-filter http N2H2 allowmode enable command [20](#)

url-filter http smartfilter enable command [39](#)

url-filter http websense allowmode enable command [36](#)

url-filter http websense server command [36](#)

## URL filtering

- disabling bypass options [12](#)

- RADIUS [12](#)

- with N2H2 server [12](#)

url-filter rtsp bad-sites-deny file command [15](#)

url-filter rtsp command [15](#)

url-filter rtsp good-sites-allow enable command [15](#)

url-filter rtsp good-sites-allow file command [15](#)

url-filter wmt bad-sites-deny file command 15  
url-filter wmt command 15  
url-filter wmt good-sites-allow enable command 15  
url-filter wmt good-sites-allow file command 15  
URLs  
    monitoring 5  
user accounts  
    default account 3  
    managing 19  
username command 8  
UTC  
    clock EXEC command 4

---

## V

variable bit rates 24

---

## W

### WCCP

accelerated 34  
access lists 10  
advanced caching features 14  
clean shutdown 18  
configuring  
    home router 41  
    user-defined services 13  
defining router lists 12  
displaying  
    configured services 41  
    list of recognized routers 17  
enabling  
    on a Content Engine 2  
    on routers 23  
enabling on Content Engine 12  
flow protection 9  
flow redirection 10  
information, displaying 42

IP spoofing 10  
overview of 2  
packet flow diagram 2  
redirected HTTP traffic, accepting 20  
shutting down 17  
transparent forward proxy caching with 9  
Version 1  
    enabling on a router 20  
Version 2  
    enabling on a router 20  
    multirouter support 8  
wccp 14  
wccp access-list command 7, 20  
WCCP access lists  
    configuring 7, 20  
    displaying 7, 20  
WCCP clustering  
    setting parameters for 2  
wccp command 10  
WCCP-enabled routers  
    forward proxy caching and 9  
    reverse proxy caching and 10  
WCCP flow protection  
    configuring 9  
    description of 2  
    displaying summary information about 9  
wccp flow-redirect command  
    for WCCP flow protection 9  
WCCP flow redirection  
    enabling and disabling 17  
wccp home-router command 41  
wccp https-cache accept-all command 11, 28  
wccp https-cache mask command 36, 37  
wccp masks  
    displaying configurations for 37  
wccp port-list command 12  
wccp router-list command 13  
WCCP service groups  
    controlling membership to 23

- WCCP services
  - configuring
    - hashing methods [35, 36](#)
    - masks for [35, 36](#)
    - port lists for [12](#)
    - router lists for [13](#)
    - user-defined services [15](#)
  - displaying list of [10](#)
  - dynamic WCCP services [14](#)
  - list of [3](#)
  - predefined WCCP services [14](#)
  - service names [4](#)
  - service numbers [4](#)
  - user-defined [14](#)
- wccp shutdown max-wait command [18](#)
- WCCP slow start
  - description of [2](#)
- wccp slow-start enable command
  - WCCP slow start [10](#)
- wccp spoof-client-ip enable command [11](#)
- WCCP transparent redirection
  - overview of [2](#)
- WCCP Version 1
  - overview of [2](#)
- WCCP Version 1 commands
  - debug ip wccp packets [42](#)
  - show ip interface [39, 41](#)
  - show ip wccp web-caches [42](#)
  - show wccp [42](#)
- WCCP Version 2
  - Cisco Express Forwarding (CEF) [7](#)
  - overview of [2](#)
- WCCP Version 2 command
  - clear ip wccp [34](#)
  - show wccp [17](#)
- wccp web-cache router-list command [14](#)
- web cache packet return [6](#)
- web objects
  - description of [2](#)
- Websense server
  - CLI commands [26](#)
  - failover [22](#)
  - port configuration [28](#)
  - websense-server enable command [35](#)
  - websense-server ip-address command [26](#)
  - websense-server service edir-agent edir-server administrative-passwd command [26](#)
  - websense-server service eim activate command [26](#)
  - websense-server service network-agent activate command [26](#)
  - websense-server service policy local activate command [26](#)
  - websense-server service policy remote command [26](#)
  - websense-server service user activate command [26](#)
  - websense-server user-server external command [26](#)
- Websense services
  - activating [34](#)
  - deactivating [37](#)
  - supported services [24](#)
- web server acceleration [10](#)
- wildcard character \* [7](#)
- WMT
  - caching overview [2](#)
  - components of [2](#)
  - configuring
    - fast cache [29](#)
    - fast start [28](#)
  - description of [9](#)
  - displaying request statistics [47](#)
  - error logging [11](#)
  - Fast Cache
    - configuring on Content Engines [31](#)
  - Fast Start
    - configuring on Content Engines [29](#)
  - multicasting
    - multicast-in and multicast-out [43](#)
    - multicast-in and unicast-out [43](#)
    - unicast-in and multicast-out [43](#)
  - multicast logging [48](#)

- removing license key [11](#)
- transaction logging [10, 48](#)
- unicasting
  - unicast-in and unicast-out [44](#)
- wmt accelerate command [21](#)
- wmt accelerate live-split enable command [21](#)
- wmt accelerate proxy-cache enable command [21](#)
- wmt accelerate VOD enable command [21](#)
- wmt bandwidth incoming bypass-list command [26](#)
- wmt broadcast command [43](#)
- wmt cache enable command [35](#)
- wmt cache max-obj-size command [19, 34, 35](#)
- WMT caching proxy
  - live splitting [10](#)
  - proxy authentication [10](#)
  - variable bit rate support [10](#)
- wmt disallowed-client-protocols command [18](#)
- WMT error logging [55](#)
- wmt extended transaction-log enable command [54](#)
- wmt fast-cache enable command
  - Fast Cache feature
    - reenabling [31](#)
- wmt fast-proxy-cache command [29](#)
- wmt fast-start command [28](#)
- wmt http allow extension command [20](#)
- WMT license key
  - removing [31, 13](#)
- WMT live splitting
  - accelerating delivery of [21](#)
- wmt max-bandwidth command [19](#)
- wmt max-bitrate command [19](#)
- WMT multicast-in multicast out
  - configuring [38](#)
  - description of [38](#)
- WMT multicast-in unicast out
  - configuring [43](#)
  - description of [43](#)
- wmt multicast log command [48](#)
- WMT multicasts
  - source failover for [42](#)
  - sources of [41](#)
- WMT multicasts, types of
  - multicast-in multicast-out [38, 39](#)
  - multicast-in unicast-out [43](#)
  - unicast-in unicast-out [44](#)
- wmt multicast schedule-start command [41](#)
- wmt multicast-station command [42](#)
- wmt multicast station-configuration station-name failover command [42](#)
- WMT multicast stations
  - configuring schedules for [43](#)
  - starting and stopping [41](#)
- wmt multicast time-to-live command
  - WMT multicasts
    - TTL for [38](#)
- WMT proxy caching
  - accelerating delivery of [21](#)
  - configuring
    - through Content Engine CLI [15](#)
    - through Setup utility [15](#)
- wmt proxy outgoing http host command [11, 19](#)
- WMT streaming and caching
  - displaying WMT statistics [47](#)
- WMT streaming and caching services
  - description of [5](#)
  - list of [5](#)
- WMT streams
  - accelerating delivery of [21](#)
  - clearing on Content Engine [45](#)
- WMT transaction log
  - logging usernames [54](#)
  - specifying format of [50](#)
- wmt transaction-logs format command [50](#)
- WMT transparent caching
  - configuring
    - through CLI [15](#)
    - through Setup utility [15](#)
- WMT unicast-in multicast out

- configuring [39](#)
- description of [39](#)
- WMT unicast-in unicast out
  - configuring [44](#)
  - description of [44](#)
- WMT VOD files
  - accelerating delivery of [21](#)
- write memory command [13](#)

