



Numerics

- 10-Gigabit Ethernet interfaces
 - configuration guidelines [11-16](#)
 - defined [11-6](#)

A

- abbreviating commands [2-4](#)
- ABRs [35-25](#)
- access-class command [32-20](#)
- access control entries
 - See ACEs
- access-denied response, VMPS [13-28](#)
- access groups
 - applying IPv4 ACLs to interfaces [32-21](#)
 - Layer 2 [32-21](#)
 - Layer 3 [32-21](#)
- accessing stack members [5-22](#)
- access lists
 - See ACLs
- access ports
 - and Layer 2 protocol tunneling [17-11](#)
 - defined [11-3](#)
- accounting
 - with 802.1x [10-25](#)
 - with IEEE 802.1x [10-5](#)
 - with RADIUS [9-28](#)
 - with TACACS+ [9-11, 9-16](#)

ACEs

- and QoS [33-7](#)
- defined [32-2](#)
- Ethernet [32-2](#)
- IP [32-2](#)

ACLs

- ACEs [32-2](#)
- any keyword [32-12](#)
- applying
 - on bridged packets [32-39](#)
 - on multicast packets [32-40](#)
 - on routed packets [32-39](#)
 - on switched packets [32-38](#)
 - time ranges to [32-17](#)
 - to an interface [32-20](#)
 - to QoS [33-7](#)
- classifying traffic for QoS [33-43](#)
- comments in [32-19](#)
- compiling [32-22](#)
- defined [32-1, 32-8](#)
- examples of [32-22, 33-43](#)
- extended IP
 - configuring for QoS classification [33-44](#)
- extended IPv4
 - creating [32-11](#)
 - matching criteria [32-8](#)
- hardware and software handling [32-22](#)
- host keyword [32-13](#)

ACLs (continued)

IP

- creating 32-8
- fragments and QoS guidelines 33-33
- implicit deny 32-10, 32-14, 32-16
- implicit masks 32-10
- matching criteria 32-8
- undefined 32-21

IPv4

- applying to interfaces 32-20
- creating 32-8
- matching criteria 32-8
- named 32-15
- numbers 32-8
- terminal lines, setting on 32-19
- unsupported features 32-7

Layer 4 information in 32-38

logging messages 32-9

MAC extended 32-27, 33-45

matching 32-8, 32-21

monitoring 32-41

named, IPv4 32-15

number per QoS class map 33-33

port 32-2

precedence of 32-2

QoS 33-7, 33-43

resequencing entries 32-15

router 32-2

router ACLs and VLAN map configuration
guidelines 32-37

standard IP, configuring for QoS classification 33-43

standard IPv4

- creating 32-10
- matching criteria 32-8

support for 1-7

support in hardware 32-22

time ranges 32-17

types supported 32-2

unsupported features, IPv4 32-7

ACLs (continued)

using router ACLs with VLAN maps 32-37

VLAN maps

- configuration guidelines 32-30
- configuring 32-30

active links 21-1

active router 37-1

address aliasing 24-2

addresses

displaying the MAC address table 7-26

dynamic

- accelerated aging 18-9
- changing the aging time 7-21
- default aging 18-9
- defined 7-19
- learning 7-20
- removing 7-22

MAC, discovering 7-27

multicast

- group address range 38-3
- STP address management 18-9

static

- adding and removing 7-24
- defined 7-19

address resolution 7-27, 35-9

Address Resolution Protocol

See ARP

adjacency tables, with CEF 35-74

administrative distances

- defined 35-86
- OSPF 35-31
- routing protocol defaults 35-76

advanced IP services image 1-1, 36-1

advertisements

- CDP 26-1
- RIP 35-20
- VTP 13-19, 14-3

aggregatable global unicast addresses 36-3

aggregate addresses, BGP 35-58

- aggregated ports
 - See EtherChannel
- aggregate policers [33-59](#)
- aggregate policing [1-9](#)
- aggregator template [5-9, 8-1](#)
- aging, accelerating [18-9](#)
- aging time
 - accelerated
 - for MSTP [19-23](#)
 - for STP [18-9, 18-23](#)
 - MAC address table [7-21](#)
 - maximum
 - for MSTP [19-24](#)
 - for STP [18-23](#)
- alarms, RMON [29-3](#)
- allowed-VLAN list [13-22](#)
- area border routers
 - See ABRs
- ARP
 - configuring [35-10](#)
 - defined [1-5, 7-27, 35-10](#)
 - encapsulation [35-11](#)
 - static cache configuration [35-10](#)
 - table
 - address resolution [7-27](#)
 - managing [7-27](#)
- ASBRs [35-25](#)
- AS-path filters, BGP [35-52](#)
- asymmetrical links, and IEEE 802.1Q tunneling [17-4](#)
- attributes, RADIUS
 - vendor-proprietary [9-30](#)
 - vendor-specific [9-29](#)
- audience [xxxix](#)
- authentication
 - EIGRP [35-39](#)
 - HSRP [37-9](#)
 - local mode with AAA [9-36](#)
 - NTP associations [7-5](#)
- authentication (continued)
 - RADIUS
 - key [9-21](#)
 - login [9-23](#)
 - TACACS+
 - defined [9-11](#)
 - key [9-13](#)
 - login [9-14](#)
- See also port-based authentication
- authentication keys, and routing protocols [35-87](#)
- authoritative time source, described [7-2](#)
- authorization
 - with RADIUS [9-27](#)
 - with TACACS+ [9-11, 9-16](#)
- authorized ports with IEEE 802.1x [10-4](#)
- autoconfiguration [3-3](#)
- automatic advise (auto-advise) in switch stacks [5-11](#)
- automatic copy (auto-copy) in switch stacks [5-11](#)
- automatic QoS
 - See QoS
- automatic upgrades (auto-upgrade) in switch stacks [5-11](#)
- Auto-MDIX
 - configuring [11-20](#)
 - described [11-20](#)
- autonegotiation
 - duplex mode [1-3](#)
 - interface configuration guidelines [11-17](#)
 - mismatches [41-12](#)
- autonomous system boundary routers
 - See ASBRs
- autonomous systems, in BGP [35-45](#)
- Auto-RP, described [38-5](#)
- autosensing, port speed [1-3](#)
- auxiliary VLAN
 - See voice VLAN
- availability, features [1-6](#)

B

- BackboneFast
 - described 20-7
 - disabling 20-17
 - enabling 20-16
 - support for 1-6
- backup interfaces
 - See Flex Links
- backup links 21-1
- banners
 - configuring
 - login 7-19
 - message-of-the-day login 7-18
 - default configuration 7-17
 - when displayed 7-17
- BGP
 - aggregate addresses 35-58
 - aggregate routes, configuring 35-58
 - CIDR 35-58
 - clear commands 35-62
 - community filtering 35-55
 - configuring neighbors 35-56
 - default configuration 35-43
 - described 35-42
 - enabling 35-45
 - monitoring 35-62
 - multipath support 35-49
 - neighbors, types of 35-45
 - path selection 35-49
 - peers, configuring 35-56
 - prefix filtering 35-54
 - resetting sessions 35-48
 - route dampening 35-61
 - route maps 35-51
 - route reflectors 35-59
 - routing domain confederation 35-59
 - routing session with multi-VRF CE 35-68
 - show commands 35-62
 - BGP (continued)
 - supernets 35-58
 - support for 1-10
 - Version 4 35-42
 - binding cluster group and HSRP group 37-11
 - binding database
 - address, DHCP server
 - See DHCP, Cisco IOS server database
 - DHCP snooping
 - See DHCP snooping binding database
 - bindings
 - address, Cisco IOS DHCP server 22-5
 - DHCP snooping database 22-6
 - IP source guard 22-14
 - binding table, DHCP snooping
 - See DHCP snooping binding database
 - blocking packets 25-6
 - booting
 - boot loader, function of 3-2
 - boot process 3-2
 - manually 3-13
 - specific image 3-14
 - boot loader
 - accessing 3-14
 - described 3-2
 - environment variables 3-15
 - prompt 3-14
 - trap-door mechanism 3-2
 - bootstrap router (BSR), described 38-5
 - Border Gateway Protocol
 - See BGP
 - BPDU
 - error-disabled state 20-3
 - filtering 20-3
 - RSTP format 19-12

- BPDU filtering
 - described 20-3
 - disabling 20-15
 - enabling 20-14
 - support for 1-6
 - BPDU guard
 - described 20-3
 - disabling 20-14
 - enabling 20-13
 - support for 1-6
 - bridged packets, ACLs on 32-39
 - bridge groups
 - See fallback bridging
 - bridge protocol data unit
 - See BPDU
 - broadcast flooding 35-17
 - broadcast packets
 - directed 35-14
 - flooded 35-14
 - broadcast storm-control command 25-4
 - broadcast storms 25-1, 35-14
-
- C
- cables, monitoring for unidirectional links 27-1
 - candidate switch
 - defined 6-3
 - requirements 6-3
 - See also command switch, cluster standby group, and member switch
 - CA trustpoint
 - configuring 9-45
 - defined 9-42
 - caution, described xl
- CDP
 - and trusted boundary 33-39
 - configuring 26-2
 - default configuration 26-2
 - described 26-1
 - disabling for routing device 26-3 to 26-4
 - enabling and disabling
 - on an interface 26-4
 - on a switch 26-3
 - Layer 2 protocol tunneling 17-8
 - monitoring 26-5
 - overview 26-1
 - power negotiation extensions 11-6
 - support for 1-5
 - switch stack considerations 26-2
 - transmission timer and holdtime, setting 26-2
 - updates 26-2
 - CEF
 - defined 35-74
 - distributed 35-74
 - enabling 35-74
 - IPv6 36-15
 - CGMP
 - as IGMP snooping learning method 24-8
 - clearing cached group entries 38-50
 - enabling server support 38-33
 - joining multicast group 24-3
 - overview 38-8
 - server support only 38-8
 - switch support of 1-4
 - CIDR 35-58
 - CipherSuites 9-43
 - Cisco 7960 IP Phone 15-1
 - Cisco Discovery Protocol
 - See CDP
 - Cisco Express Forwarding
 - See CEF
 - Cisco Group Management Protocol
 - See CGMP

- Cisco Intelligence Engine 2100 Series Configuration Registrar
 - See IE2100
- Cisco intelligent power management [11-6](#)
- Cisco IOS DHCP server
 - See DHCP, Cisco IOS DHCP server
- Cisco IOS File System
 - See IFS
- Cisco Network Assistant
 - See Network Assistant
- Cisco Networking Services
 - See IE2100
- Cisco StackWise technology [1-3](#)
 - See also stacks, switch
- CiscoWorks 2000 [1-5, 31-4](#)
- CIST regional root
 - See MSTP
- CIST root
 - See MSTP
- classless interdomain routing
 - See CIDR
- classless routing [35-8](#)
- class maps for QoS
 - configuring [33-46](#)
 - described [33-7](#)
 - displaying [33-79](#)
- class of service
 - See CoS
- clearing interfaces [11-27](#)
- CLI
 - abbreviating commands [2-4](#)
 - command modes [2-1](#)
 - configuration logging [2-5](#)
 - described [1-4](#)
 - editing features
 - enabling and disabling [2-7](#)
 - keystroke editing [2-8](#)
 - wrapped lines [2-9](#)
 - error messages [2-5](#)
- CLI (continued)
 - filtering command output [2-10](#)
 - getting help [2-3](#)
 - history
 - changing the buffer size [2-6](#)
 - described [2-6](#)
 - disabling [2-7](#)
 - recalling commands [2-6](#)
 - managing clusters [6-4](#)
 - no and default forms of commands [2-4](#)
- client mode, VTP [14-3](#)
- clock
 - See system clock
- cluster requirements [xli](#)
- clusters, switch
 - benefits [1-2](#)
 - described [6-1](#)
 - managing
 - through CLI [6-4](#)
 - through SNMP [6-5](#)
 - planning considerations
 - CLI [6-4](#)
 - SNMP [6-5](#)
- See also Getting Started with Cisco Network Assistant
- cluster standby group
 - and HSRP group [37-11](#)
 - requirements [6-2](#)
- Coarse Wave Division Multiplexer
 - See CWDM SFPs
- command-line interface
 - See CLI
- command modes [2-1](#)
- commands
 - abbreviating [2-4](#)
 - no and default [2-4](#)
- commands, setting privilege levels [9-8](#)

- command switch
 - configuration conflicts [41-12](#)
 - defined [6-2](#)
 - password privilege levels [6-4](#)
 - recovery
 - from command-switch failure [41-8](#)
 - from lost member connectivity [41-12](#)
 - replacing
 - with another switch [41-11](#)
 - with cluster member [41-9](#)
 - requirements [6-2](#)
 - See also candidate switch, cluster standby group, member switch, and standby command switch
- community list, BGP [35-55](#)
- community ports [16-2](#)
- community strings
 - configuring [31-8](#)
 - for cluster switches [31-4](#)
 - overview [31-4](#)
- community VLANs [16-2, 16-3](#)
- compatibility, feature [25-11](#)
- compatibility, software
 - See stacks, switch
- config.text [3-12](#)
- configurable leave timer, IGMP [24-5](#)
- configuration, initial
 - defaults [1-11](#)
 - Express Setup [1-2](#)
 - See also getting started guide and hardware installation guide
- configuration conflicts, recovering from lost member connectivity [41-12](#)
- configuration examples, network [1-14](#)
- configuration files
 - clearing the startup configuration [B-19](#)
 - creating using a text editor [B-10](#)
 - default name [3-12](#)
 - deleting a stored configuration [B-19](#)
 - described [B-8](#)
- configuration files (continued)
 - downloading
 - automatically [3-12](#)
 - preparing [B-11, B-13, B-16](#)
 - reasons for [B-9](#)
 - using FTP [B-13](#)
 - using RCP [B-17](#)
 - using TFTP [B-11](#)
 - guidelines for creating and using [B-9](#)
 - invalid combinations when copying [B-5](#)
 - limiting TFTP server access [31-15](#)
 - obtaining with DHCP [3-7](#)
 - password recovery disable considerations [9-5](#)
 - specifying the filename [3-12](#)
 - system contact and location information [31-14](#)
 - types and location [B-10](#)
 - uploading
 - preparing [B-11, B-13, B-16](#)
 - reasons for [B-9](#)
 - using FTP [B-14](#)
 - using RCP [B-18](#)
 - using TFTP [B-12](#)
- configuration guidelines, multi-VRF CE [35-66](#)
- configuration logging [2-5](#)
- configuration settings, saving [3-10](#)
- configure terminal command [11-11](#)
- config-vlan mode [2-2, 13-7](#)
- conflicts, configuration [41-12](#)
- connections, secure remote [9-38](#)
- connectivity problems [41-14, 41-16, 41-17](#)
- consistency checks in VTP Version 2 [14-4](#)
- console port, connecting to [2-11](#)
- conventions
 - command [xl](#)
 - for examples [xl](#)
 - publication [xl](#)
 - text [xl](#)
- corrupted software, recovery steps with Xmodem [41-2](#)

- CoS
 - in Layer 2 frames [33-2](#)
 - override priority [15-6](#)
 - trust priority [15-6](#)
 - CoS input queue threshold map for QoS [33-16](#)
 - CoS output queue threshold map for QoS [33-19](#)
 - CoS-to-DSCP map for QoS [33-61](#)
 - counters, clearing interface [11-27](#)
 - crashinfo file [41-24](#)
 - cross-stack EtherChannel
 - configuration guidelines [34-12](#)
 - configuring
 - on Layer 2 interfaces [34-12](#)
 - on Layer 3 physical interfaces [34-15](#)
 - described [34-2](#)
 - illustration [34-3](#)
 - support for [1-6](#)
 - cross-stack UplinkFast, STP
 - described [20-5](#)
 - disabling [20-16](#)
 - enabling [20-16](#)
 - fast-convergence events [20-7](#)
 - Fast Uplink Transition Protocol [20-6](#)
 - normal-convergence events [20-7](#)
 - support for [1-6](#)
 - cryptographic software image
 - Kerberos [9-32](#)
 - SSH [9-37](#)
 - SSL [9-42](#)
 - switch stack considerations [5-2, 5-16, 9-38](#)
 - customer edge devices [35-64](#)
 - CWDM SFPs [1-24](#)
-
- D
 - daylight saving time [7-13](#)
 - dCEF
 - in the switch stack [35-74](#)
 - debugging
 - enabling all system diagnostics [41-21](#)
 - enabling for a specific feature [41-20](#)
 - redirecting error message output [41-21](#)
 - using commands [41-20](#)
 - default commands [2-4](#)
 - default configuration
 - 802.1x [10-13](#)
 - auto-QoS [33-20](#)
 - banners [7-17](#)
 - BGP [35-43](#)
 - booting [3-12](#)
 - CDP [26-2](#)
 - DHCP [22-7](#)
 - DHCP option 82 [22-7](#)
 - DHCP snooping [22-7](#)
 - DHCP snooping binding database [22-8](#)
 - DNS [7-16](#)
 - dynamic ARP inspection [23-5](#)
 - EIGRP [35-36](#)
 - EtherChannel [34-10](#)
 - Ethernet interfaces [11-15](#)
 - fallback bridging [40-4](#)
 - Flex Links [21-2](#)
 - HSRP [37-5](#)
 - IEEE 802.1Q tunneling [17-4](#)
 - IGMP [38-27](#)
 - IGMP filtering [24-22](#)
 - IGMP snooping [24-7](#)
 - IGMP throttling [24-22](#)
 - initial switch information [3-3](#)
 - IP addressing, IP routing [35-6](#)
 - IP multicast routing [38-9](#)
 - IP source guard [22-15](#)
 - IPv6 [36-11](#)
 - Layer 2 interfaces [11-15](#)
 - Layer 2 protocol tunneling [17-11](#)
 - MAC address table [7-21](#)
 - MSDP [39-4](#)

- default configuration (continued)
 - MSTP 19-15
 - multi-VRF CE 35-65
 - MVR 24-17
 - NTP 7-4
 - optional spanning-tree configuration 20-12
 - OSPF 35-26
 - password and privilege level 9-2
 - PIM 38-9
 - private VLANs 16-6
 - RADIUS 9-20
 - RIP 35-21
 - RMON 29-3
 - RSPAN 28-11
 - SDM template 8-5
 - SNMP 31-6
 - SPAN 28-11
 - SSL 9-44
 - standard QoS 33-31
 - STP 18-13
 - switch stacks 5-19
 - system message logging 31-4
 - system name and prompt 7-15
 - TACACS+ 9-13
 - UDLD 27-4
 - VLAN, Layer 2 Ethernet interfaces 13-19
 - VLANs 13-8
 - VMPS 13-29
 - voice VLAN 15-3
 - VTP 14-7
- default gateway 3-10, 35-12
- default networks 35-77
- default routes 35-77
- default routing 35-3
- deleting VLANs 13-10
- denial-of-service attack 25-1
- description command 11-22
- designing your network, examples 1-14
- desktop template 5-9, 8-1
- destination addresses, in IPv4 ACLs 32-12
- destination-IP address-based forwarding, EtherChannel 34-8
- destination-MAC address forwarding, EtherChannel 34-8
- detecting indirect link failures, STP 20-8
- device B-19
- device discovery protocol 26-1
- device manager
 - benefits 1-2
 - described 1-2, 1-4
 - in-band management 1-5
 - requirements xl
 - upgrading a switch B-19
- DHCP
 - Cisco IOS server database
 - configuring 22-13
 - default configuration 22-8
 - described 22-5
 - enabling
 - relay agent 22-9
 - server 22-9
- DHCP-based autoconfiguration
 - client request message exchange 3-4
 - configuring
 - client side 3-4
 - DNS 3-6
 - relay device 3-7
 - server side 3-5
 - server-side 22-9
 - TFTP server 3-6
 - example 3-8
 - lease options
 - for IP address information 3-5
 - for receiving the configuration file 3-5
 - overview 3-3
 - relationship to BOOTP 3-4
 - relay support 1-5, 1-10
 - support for 1-5

- DHCP binding database
 - See DHCP snooping binding database
- DHCP binding table
 - See DHCP snooping binding database
- DHCP option 82
 - circuit ID suboption [22-5](#)
 - configuration guidelines [22-8](#)
 - default configuration [22-7](#)
 - displaying [22-14](#)
 - forwarding address, specifying [22-10](#)
 - helper address [22-10](#)
 - overview [22-3](#)
 - packet format, suboption
 - circuit ID [22-5](#)
 - remote ID [22-5](#)
 - remote ID suboption [22-5](#)
- DHCP snooping
 - accepting untrusted packets from edge switch [22-3](#), [22-11](#)
 - and private VLANs [22-12](#)
 - binding database
 - See DHCP snooping binding database
 - configuration guidelines [22-8](#)
 - default configuration [22-7](#)
 - displaying binding tables [22-14](#)
 - message exchange process [22-4](#)
 - option 82 data insertion [22-3](#)
 - trusted interface [22-2](#)
 - untrusted interface [22-2](#)
 - untrusted messages [22-2](#)
- DHCP snooping binding database
 - adding bindings [22-13](#)
 - binding file
 - format [22-6](#)
 - location [22-6](#)
 - bindings [22-6](#)
 - clearing agent statistics [22-14](#)
 - configuration guidelines [22-9](#)
 - configuring [22-13](#)
- DHCP snooping binding database (continued)
 - default configuration [22-7](#), [22-8](#)
 - deleting
 - binding file [22-14](#)
 - bindings [22-14](#)
 - database agent [22-14](#)
 - described [22-5](#)
 - displaying [22-14](#)
 - binding entries [22-14](#)
 - status and statistics [22-14](#)
 - enabling [22-13](#)
 - entry [22-6](#)
 - renewing database [22-14](#)
 - resetting
 - delay value [22-14](#)
 - timeout value [22-14](#)
- DHCP snooping binding table
 - See DHCP snooping binding database
- Differentiated Services architecture, QoS [33-2](#)
- Differentiated Services Code Point [33-2](#)
- Diffusing Update Algorithm (DUAL) [35-34](#)
- directed unicast requests [1-5](#)
- directories
 - changing [B-4](#)
 - creating and removing [B-4](#)
 - displaying the working [B-4](#)
- Distance Vector Multicast Routing Protocol
 - See DVMRP
- distance-vector protocols [35-3](#)
- distribute-list command [35-85](#)
- DNS
 - and DHCP-based autoconfiguration [3-6](#)
 - default configuration [7-16](#)
 - displaying the configuration [7-17](#)
 - in IPv6 [36-4](#)
 - overview [7-15](#)
 - setting up [7-16](#)
 - support for [1-5](#)
- documentation, related [xl](#)

- document conventions [xl](#)
- domain names
 - DNS [7-15](#)
 - VTP [14-8](#)
- Domain Name System
 - See DNS
- dot1q-tunnel switchport mode [13-18](#)
- double-tagged packets
 - IEEE 802.1Q tunneling [17-2](#)
 - Layer 2 protocol tunneling [17-10](#)
- downloading
 - configuration files
 - preparing [B-11, B-13, B-16](#)
 - reasons for [B-9](#)
 - using FTP [B-13](#)
 - using RCP [B-17](#)
 - using TFTP [B-11](#)
 - image files
 - deleting old image [B-23](#)
 - preparing [B-21, B-25, B-29](#)
 - reasons for [B-19](#)
 - using CMS [1-2](#)
 - using FTP [B-26](#)
 - using HTTP [1-2, B-19](#)
 - using RCP [B-31](#)
 - using TFTP [B-22](#)
 - using the device manager or Network Assistant [B-19](#)
- drop threshold for Layer 2 protocol packets [17-11](#)
- DSCP [1-9, 33-2](#)
- DSCP input queue threshold map for QoS [33-16](#)
- DSCP output queue threshold map for QoS [33-19](#)
- DSCP-to-CoS map for QoS [33-64](#)
- DSCP-to-DSCP-mutation map for QoS [33-65](#)
- DSCP transparency [33-39](#)
- DTP [1-7, 13-17](#)
- DUAL finite state machine, EIGRP [35-35](#)
- dual IPv4 and IPv6 templates [8-2, 36-9](#)
- dual protocol stacks
 - configuring [36-13](#)
 - IPv4 and IPv6 [36-8](#)
 - SDM templates supporting [36-9](#)
- duplex mode, configuring [11-17](#)
- DVMRP
 - autosummarization
 - configuring a summary address [38-47](#)
 - disabling [38-49](#)
 - connecting PIM domain to DVMRP router [38-39](#)
 - enabling unicast routing [38-43](#)
 - interoperability
 - with Cisco devices [38-37](#)
 - with Cisco IOS software [38-7](#)
 - mrinfo requests, responding to [38-42](#)
 - neighbors
 - advertising the default route to [38-41](#)
 - discovery with Probe messages [38-37](#)
 - displaying information [38-42](#)
 - prevent peering with nonpruning [38-45](#)
 - rejecting nonpruning [38-43](#)
 - overview [38-7](#)
 - routes
 - adding a metric offset [38-49](#)
 - advertising all [38-49](#)
 - advertising the default route to neighbors [38-41](#)
 - caching DVMRP routes learned in report messages [38-43](#)
 - changing the threshold for syslog messages [38-46](#)
 - deleting [38-50](#)
 - displaying [38-51](#)
 - favoring one over another [38-49](#)
 - limiting the number injected into MBONE [38-46](#)
 - limiting unicast route advertisements [38-37](#)
 - routing table [38-7](#)
 - source distribution tree, building [38-7](#)
 - support for [1-10](#)

- DVMRP (continued)
 - tunnels
 - configuring [38-39](#)
 - displaying neighbor information [38-42](#)
- dynamic access ports
 - characteristics [13-3](#)
 - configuring [13-31](#)
 - defined [11-3](#)
- dynamic addresses
 - See addresses
- dynamic ARP inspection
 - ARP cache poisoning [23-1](#)
 - ARP requests, described [23-1](#)
 - ARP spoofing attack [23-1](#)
 - clearing
 - log buffer [23-15](#)
 - statistics [23-15](#)
 - configuration guidelines [23-6](#)
 - configuring
 - ACLs for non-DHCP environments [23-8](#)
 - in DHCP environments [23-7](#)
 - log buffer [23-12](#)
 - rate limit for incoming ARP packets [23-4, 23-10](#)
 - default configuration [23-5](#)
 - denial-of-service attacks, preventing [23-10](#)
 - described [23-1](#)
 - DHCP snooping binding database [23-2](#)
 - displaying
 - ARP ACLs [23-14](#)
 - configuration and operating state [23-14](#)
 - log buffer [23-15](#)
 - statistics [23-15](#)
 - trust state and rate limit [23-14](#)
 - error-disabled state for exceeding rate limit [23-4](#)
 - function of [23-2](#)
 - interface trust states [23-3](#)
- dynamic ARP inspection (continued)
 - log buffer
 - clearing [23-15](#)
 - configuring [23-12](#)
 - displaying [23-15](#)
 - logging of dropped packets, described [23-5](#)
 - man-in-the middle attack, described [23-2](#)
 - network security issues and interface trust states [23-3](#)
 - priority of ARP ACLs and DHCP snooping entries [23-4](#)
 - rate limiting of ARP packets
 - configuring [23-10](#)
 - described [23-4](#)
 - error-disabled state [23-4](#)
 - statistics
 - clearing [23-15](#)
 - displaying [23-15](#)
 - validation checks, performing [23-11](#)
- dynamic auto trunking mode [13-18](#)
- dynamic desirable trunking mode [13-18](#)
- Dynamic Host Configuration Protocol
 - See DHCP-based autoconfiguration
- dynamic port VLAN membership
 - described [13-29](#)
 - reconfirming [13-31](#)
 - troubleshooting [13-33](#)
 - types of connections [13-31](#)
- dynamic routing [35-3](#)
- Dynamic Trunking Protocol
 - See DTP

E

- EBGP [35-41](#)
- editing features
 - enabling and disabling [2-7](#)
 - keystrokes used [2-8](#)
 - wrapped lines [2-9](#)

EIGRP

- authentication [35-39](#)
- components [35-35](#)
- configuring [35-38](#)
- default configuration [35-36](#)
- definition [35-34](#)
- interface parameters, configuring [35-38](#)
- monitoring [35-40](#)
- support for [1-10](#)

elections

See stack master

- enable password [9-3](#)
- enable secret password [9-3](#)
- encryption, CipherSuite [9-44](#)
- encryption for passwords [9-3](#)

Enhanced IGRP

See EIGRP

- environment variables, function of [3-15](#)
- equal-cost routing [1-10, 35-75](#)
- error messages during command entry [2-5](#)

EtherChannel

- automatic creation of [34-5, 34-6](#)
- channel groups
 - binding physical and logical interfaces [34-4](#)
 - numbering of [34-4](#)
- configuration guidelines [34-11](#)
- configuring
 - Layer 2 interfaces [34-12](#)
 - Layer 3 physical interfaces [34-15](#)
 - Layer 3 port-channel logical interfaces [34-14](#)
- default configuration [34-10](#)
- described [34-2](#)
- displaying status [34-21](#)
- forwarding methods [34-7, 34-17](#)
- IEEE 802.3ad, described [34-6](#)
- interaction
 - with STP [34-11](#)
 - with VLANs [34-11](#)

EtherChannel (continued)

LACP

- described [34-6](#)
- displaying status [34-21](#)
- hot-standby ports [34-19](#)
- interaction with other features [34-7](#)
- modes [34-7](#)
- port priority [34-20](#)
- system priority [34-20](#)

Layer 3 interface [35-5](#)

load balancing [34-7, 34-17](#)

logical interfaces, described [34-4](#)

PAGP

- aggregate-port learners [34-18](#)
- compatibility with Catalyst 1900 [34-18](#)
- described [34-5](#)
- displaying status [34-21](#)
- interaction with other features [34-6](#)
- learn method and priority configuration [34-18](#)
- modes [34-5](#)
- support for [1-4](#)
- port-channel interfaces
 - described [34-4](#)
 - numbering of [34-4](#)
- port groups [11-5](#)
- stack changes, effects of [34-9](#)
- support for [1-4](#)

EtherChannel guard

- described [20-10](#)
- disabling [20-17](#)
- enabling [20-17](#)

Ethernet VLANs

- adding [13-8](#)
- defaults and ranges [13-8](#)
- modifying [13-8](#)

EUI [36-3](#)

events, RMON [29-3](#)

examples

- conventions for [xl](#)

- network configuration [1-14](#)

expedite queue for QoS [33-78](#)

Express Setup [1-2](#)

- See also getting started guide

extended-range VLANs

- configuration guidelines [13-12](#)

- configuring [13-12](#)

- creating [13-13](#)

- creating with an internal VLAN ID [13-14](#)

- defined [13-1](#)

extended system ID

- MSTP [19-17](#)

- STP [18-4, 18-16](#)

extended universal identifier

- See EUI

Extensible Authentication Protocol over LAN [10-1](#)

external BGP

- See EBGp

external neighbors, BGP [35-45](#)

F

failover support [1-6](#)

fallback bridging

- and protected ports [40-4](#)

bridge groups

- creating [40-4](#)

- described [40-2](#)

- displaying [40-11](#)

- function of [40-2](#)

- number supported [40-5](#)

- removing [40-5](#)

bridge table

- clearing [40-11](#)

- displaying [40-11](#)

- configuration guidelines [40-4](#)

- connecting interfaces with [11-9](#)

fallback bridging (continued)

- default configuration [40-4](#)

- described [40-1](#)

frame forwarding

- flooding packets [40-2](#)

- forwarding packets [40-2](#)

- overview [40-1](#)

- protocol, unsupported [40-4](#)

- stack changes, effects of [40-3](#)

STP

- disabling on an interface [40-11](#)

- forward-delay interval [40-10](#)

- hello BPDU interval [40-9](#)

- interface priority [40-7](#)

- keepalive messages [18-2](#)

- maximum-idle interval [40-10](#)

- path cost [40-8](#)

- VLAN-bridge spanning-tree priority [40-7](#)

- VLAN-bridge STP [40-2](#)

- support for [1-10](#)

- SVIs and routed ports [40-1](#)

- unsupported protocols [40-4](#)

- VLAN-bridge STP [18-11](#)

Fast Uplink Transition Protocol [20-6](#)

features, incompatible [25-11](#)

FIB [35-74](#)

fiber-optic, detecting unidirectional links [27-1](#)

files

- copying [B-5](#)

crashinfo

- description [41-24](#)

- displaying the contents of [41-24](#)

- location [41-24](#)

- deleting [B-5](#)

- displaying the contents of [B-8](#)

- files (continued)
 - tar
 - creating [B-6](#)
 - displaying the contents of [B-7](#)
 - extracting [B-7](#)
 - image file format [B-20](#)
 - file system
 - displaying available file systems [B-2](#)
 - displaying file information [B-3](#)
 - local file system names [B-1](#)
 - network file system names [B-5](#)
 - setting the default [B-3](#)
 - filtering
 - in a VLAN [32-30](#)
 - non-IP traffic [32-27](#)
 - show and more command output [2-10](#)
 - filtering show and more command output [2-10](#)
 - filters, IP
 - See ACLs, IP
 - flash device, number of [B-1](#)
 - Flex Links
 - configuration guidelines [21-2](#)
 - configuring [21-3](#)
 - default configuration [21-2](#)
 - description [21-1](#)
 - monitoring [21-3](#)
 - flooded traffic, blocking [25-7](#)
 - flow-based packet classification [1-9](#)
 - flowcharts
 - QoS classification [33-6](#)
 - QoS egress queueing and scheduling [33-17](#)
 - QoS ingress queueing and scheduling [33-15](#)
 - QoS policing and marking [33-10](#)
 - flowcontrol
 - configuring [11-19](#)
 - described [11-19](#)
 - forward-delay time
 - MSTP [19-23](#)
 - STP [18-23](#)
 - Forwarding Information Base
 - See FIB
 - forwarding nonroutable protocols [40-1](#)
 - FTP
 - accessing MIB files [A-3](#)
 - configuration files
 - downloading [B-13](#)
 - overview [B-12](#)
 - preparing the server [B-13](#)
 - uploading [B-14](#)
 - image files
 - deleting old image [B-28](#)
 - downloading [B-26](#)
 - preparing the server [B-25](#)
 - uploading [B-28](#)
-
- G
 - get-bulk-request operation [31-3](#)
 - get-next-request operation [31-3, 31-4](#)
 - get-request operation [31-3, 31-4](#)
 - get-response operation [31-3](#)
 - Gigabit modules
 - See SFPs
 - global configuration mode [2-2](#)
 - guest VLAN and 802.1x [10-10](#)
 - guide
 - audience [xxxix](#)
 - purpose of [xxxix](#)
 - guide mode [1-2](#)
 - GUIs
 - See device manager and Network Assistant [1-4](#)

H

hardware limitations and Layer 3 interfaces [11-23](#)

hello time

- MSTP [19-22](#)
- STP [18-22](#)

help, for the command line [2-3](#)

hierarchical policy maps [33-8](#)

- configuration guidelines [33-33](#)
- configuring [33-52](#)
- described [33-11](#)

history

- changing the buffer size [2-6](#)
- described [2-6](#)
- disabling [2-7](#)
- recalling commands [2-6](#)

history table, level and number of syslog messages [31-10](#)

host ports

- configuring [16-11](#)
- kinds of [16-2](#)

hosts, limit on dynamic ports [13-33](#)

Hot Standby Router Protocol

- See HSRP

HP OpenView [1-5](#)

HSRP

- authentication string [37-9](#)
- binding to cluster group [37-11](#)
- command-switch redundancy [1-1, 1-6](#)
- configuring [37-4](#)
- default configuration [37-5](#)
- definition [37-1](#)
- guidelines [37-5](#)
- monitoring [37-11](#)
- overview [37-1](#)
- priority [37-7](#)
- routing redundancy [1-10](#)
- support for ICMP redirect messages [37-11](#)
- switch stack considerations [37-4](#)

HSRP (continued)

- timers [37-9](#)
- tracking [37-7](#)

HTTP over SSL

- see HTTPS

HTTPS [9-42](#)

- configuring [9-46](#)
- self-signed certificate [9-43](#)

HTTP secure server [9-42](#)

I

IBPG [35-41](#)

ICMP

- IPv6 [36-4](#)
- redirect messages [35-12](#)
- support for [1-10](#)
- time-exceeded messages [41-18](#)
- traceroute and [41-18](#)
- unreachable messages [32-20](#)
- unreachables and ACLs [32-22](#)

ICMP ping

- executing [41-15](#)
- overview [41-14](#)

ICMP Router Discovery Protocol

- See IRDP

ICMPv6 [36-4](#)

IDS appliances

- and ingress RSPAN [28-21](#)
- and ingress SPAN [28-14](#)

IE2100

CNS embedded agents

- described [4-5](#)
- enabling automated configuration [4-6](#)
- enabling configuration agent [4-9](#)
- enabling event agent [4-8](#)

IE2100 (continued)

Configuration Registrar

- configID, deviceID, hostname [4-3](#)

- configuration service [4-2](#)

- described [4-1](#)

- event service [4-3](#)

IEEE 802.1D

- See STP

IEEE 802.1p [15-1](#)

IEEE 802.1Q

- and trunk ports [11-3](#)

- configuration limitations [13-19](#)

- encapsulation [13-16](#)

- native VLAN for untagged traffic [13-23](#)

- tunneling

- compatibility with other features [17-6](#)

- defaults [17-4](#)

- described [17-1](#)

- tunnel ports with other features [17-6](#)

IEEE 802.1s

- See MSTP

IEEE 802.1w

- See RSTP

IEEE 802.1x

- See port-based authentication

IEEE 802.3ad

- See EtherChannel

IEEE 802.3af

- See PoE

IEEE 802.3z flow control [11-19](#)ifIndex values, SNMP [31-5](#)IFS [1-5](#)

IGMP

- configurable leave timer

- described [24-5](#)

- enabling [24-11](#)

- configuring the switch

- as a member of a group [38-27](#)

- statically connected member [38-32](#)

IGMP (continued)

- controlling access to groups [38-28](#)

- default configuration [38-27](#)

- deleting cache entries [38-51](#)

- displaying groups [38-51](#)

- fast switching [38-32](#)

- host-query interval, modifying [38-30](#)

- joining multicast group [24-3](#)

- join messages [24-3](#)

- leave processing, enabling [24-10](#)

- leaving multicast group [24-5](#)

- multicast reachability [38-27](#)

- overview [38-2](#)

- queries [24-4](#)

- report suppression

- described [24-6](#)

- disabling [24-13](#)

- supported versions [24-2](#)

- support for [1-4](#)

Version 1

- changing to Version 2 [38-29](#)

- described [38-3](#)

Version 2

- changing to Version 1 [38-29](#)

- described [38-3](#)

- maximum query response time value [38-31](#)

- pruning groups [38-31](#)

- query timeout value [38-31](#)

IGMP filtering

- configuring [24-22](#)

- default configuration [24-22](#)

- described [24-21](#)

- monitoring [24-26](#)

- support for [1-4](#)

IGMP groups

- configuring filtering [24-25](#)

- setting the maximum number [24-24](#)

IGMP profile

- applying [24-24](#)
- configuration mode [24-22](#)
- configuring [24-23](#)

IGMP snooping

- and address aliasing [24-2](#)
- and stack changes [24-6](#)
- configuring [24-6](#)
- default configuration [24-7](#)
- definition [24-1](#)
- enabling and disabling [24-7](#)
- global configuration [24-7](#)
- Immediate Leave [24-5](#)
- in the switch stack [24-6](#)
- method [24-8](#)
- monitoring [24-13](#)
- querier
 - configuration guidelines [24-12](#)
 - configuring [24-12](#)
- supported versions [24-2](#)
- support for [1-4](#)
- VLAN configuration [24-7](#)

IGMP throttling

- configuring [24-25](#)
- default configuration [24-22](#)
- described [24-22](#)
- displaying action [24-26](#)

IGP [35-25](#)

Immediate Leave, IGMP

- configuration guidelines [24-10](#)
- described [24-5](#)
- enabling [24-10](#)

initial configuration

- defaults [1-11](#)
- Express Setup [1-2](#)
- See also getting started guide and hardware installation guide

Intelligence Engine 2100 Series CNS Agents

See IE2100

interface

- number [11-10](#)
- range macros [11-13](#)

interface command [11-10 to 11-11](#)interface configuration mode [2-3](#)

interfaces

- Auto-MDIX, configuring [11-20](#)
- configuration guidelines
 - 10-Gigabit Ethernet [11-16](#)
 - duplex and speed [11-17](#)
- configuring
 - duplex mode [11-17](#)
 - procedure [11-11](#)
 - speed [11-17](#)

configuring for IPv4 and IPv6 [36-13](#)counters, clearing [11-27](#)default configuration [11-15](#)described [11-22](#)descriptive name, adding [11-22](#)displaying information about [11-26](#)flow control [11-19](#)management [1-4](#)monitoring [11-26](#)naming [11-22](#)physical, identifying [11-10](#)range of [11-11](#)restarting [11-27](#)shutting down [11-27](#)speed and duplex, configuring [11-18](#)status [11-26](#)supported [11-10](#)types of [11-1](#)interfaces range macro command [11-13](#)interface types [11-10](#)

Interior Gateway Protocol

See IGP

internal BGP

See IBGP

internal neighbors, BGP [35-45](#)

- Internet Control Message Protocol
 - See ICMP
- Internet Group Management Protocol
 - See IGMP
- Internet Protocol version 6
 - See IPv6
- Inter-Switch Link
 - See ISL
- inter-VLAN routing [1-10, 35-2](#)
- Intrusion Detection System
 - See IDS appliances
- IP ACLs
 - for QoS classification [33-7](#)
 - implicit deny [32-10, 32-14](#)
 - implicit masks [32-10](#)
 - named [32-15](#)
 - undefined [32-21](#)
- IP addresses
 - 128-bit [36-2](#)
 - candidate or member [6-3](#)
 - classes of [35-6](#)
 - command switch [6-2](#)
 - default configuration [35-6](#)
 - discovering [7-27](#)
 - for IP routing [35-5](#)
 - IPv6 [36-2](#)
 - MAC address association [35-9](#)
 - monitoring [35-18](#)
 - See also IP information
- IP base image [1-1](#)
- IP broadcast address [35-16](#)
- ip cef distributed command [35-74](#)
- IP directed broadcasts [35-15](#)
- ip igmp profile command [24-22](#)
- IP information
 - assigned
 - manually [3-10](#)
 - through DHCP-based autoconfiguration [3-3](#)
 - default configuration [3-3](#)
- IP multicast routing
 - addresses
 - all-hosts [38-3](#)
 - all-multicast-routers [38-3](#)
 - host group address range [38-3](#)
 - administratively-scoped boundaries, described [38-35](#)
 - and IGMP snooping [24-1](#)
 - Auto-RP
 - adding to an existing sparse-mode cloud [38-14](#)
 - benefits of [38-14](#)
 - clearing the cache [38-51](#)
 - configuration guidelines [38-10](#)
 - filtering incoming RP announcement messages [38-16](#)
 - overview [38-5](#)
 - preventing candidate RP spoofing [38-16](#)
 - preventing join messages to false RPs [38-16](#)
 - setting up in a new internetwork [38-14](#)
 - using with BSR [38-22](#)
 - bootstrap router
 - configuration guidelines [38-10](#)
 - configuring candidate BSRs [38-20](#)
 - configuring candidate RPs [38-21](#)
 - defining the IP multicast boundary [38-19](#)
 - defining the PIM domain border [38-18](#)
 - overview [38-5](#)
 - using with Auto-RP [38-22](#)
 - Cisco implementation [38-2](#)
 - configuring
 - basic multicast routing [38-11](#)
 - IP multicast boundary [38-35](#)
 - default configuration [38-9](#)
 - enabling
 - multicast forwarding [38-11](#)
 - PIM mode [38-12](#)
 - group-to-RP mappings
 - Auto-RP [38-5](#)
 - BSR [38-5](#)

IP multicast routing (continued)

MBONE

- deleting sdr cache entries [38-51](#)
- described [38-34](#)
- displaying sdr cache [38-52](#)
- enabling sdr listener support [38-34](#)
- limiting DVMRP routes advertised [38-46](#)
- limiting sdr cache entry lifetime [38-35](#)
- SAP packets for conference session announcement [38-34](#)
- Session Directory (sdr) tool, described [38-34](#)

monitoring

- packet rate loss [38-52](#)
- peering devices [38-52](#)
- tracing a path [38-52](#)

multicast forwarding, described [38-6](#)PIMv1 and PIMv2 interoperability [38-9](#)protocol interaction [38-2](#)reverse path check (RPF) [38-6](#)

routing table

- deleting [38-51](#)
- displaying [38-51](#)

RP

- assigning manually [38-12](#)
- configuring Auto-RP [38-14](#)
- configuring PIMv2 BSR [38-18](#)
- monitoring mapping information [38-23](#)
- using Auto-RP and BSR [38-22](#)

stacking

- stack master functions [38-8](#)
- stack member functions [38-8](#)

statistics, displaying system and network [38-51](#)

See also CGMP

See also DVMRP

See also IGMP

See also PIM

IP phones

- and QoS [15-1](#)
- automatic classification and queueing [33-20](#)
- configuring [15-4](#)
- ensuring port security with QoS [33-38](#)
- trusted boundary for QoS [33-38](#)

IP precedence [33-2](#)IP-precedence-to-DSCP map for QoS [33-62](#)

IP protocols

- in ACLs [32-12](#)
- routing [1-10](#)

IP routes, monitoring [35-88](#)

IP routing

- connecting interfaces with [11-9](#)
- disabling [35-19](#)
- enabling [35-19](#)

IP services image [1-1](#)

IP source guard

- and 802.1x [22-16](#)
- and DHCP snooping [22-14](#)
- and EtherChannels [22-16](#)
- and port security [22-16](#)
- and private VLANs [22-16](#)
- and routed ports [22-16](#)
- and TCAM entries [22-16](#)
- and trunk interfaces [22-16](#)
- and VRF [22-16](#)

binding configuration

- automatic [22-14](#)
- manual [22-14](#)

binding table [22-14](#)configuration guidelines [22-16](#)default configuration [22-15](#)described [22-14](#)disabling [22-17](#)

displaying

- bindings [22-18](#)
- configuration [22-18](#)

enabling [22-16](#)

IP source guard (continued)

filtering

source IP address 22-15

source IP and MAC address 22-15

source IP address filtering 22-15

source IP and MAC address filtering 22-15

static bindings

adding 22-16

deleting 22-17

IP traceroute

executing 41-18

overview 41-17

IP unicast routing

address resolution 35-9

administrative distances 35-76, 35-86

ARP 35-10

assigning IP addresses to Layer 3 interfaces 35-7

authentication keys 35-87

broadcast

address 35-16

flooding 35-17

packets 35-14

storms 35-14

classless routing 35-8

configuring static routes 35-75

default

addressing configuration 35-6

gateways 35-12

networks 35-77

routes 35-77

routing 35-3

directed broadcasts 35-15

disabling 35-19

dynamic routing 35-3

enabling 35-19

EtherChannel Layer 3 interface 35-5

IGP 35-25

inter-VLAN 35-2

IP unicast routing (continued)

IP addressing

classes 35-6

configuring 35-5

IPv6 36-3

IRDP 35-13

Layer 3 interfaces 35-5

MAC address and IP address 35-9

passive interfaces 35-84

protocols

distance-vector 35-3

dynamic 35-3

link-state 35-3

proxy ARP 35-10

redistribution 35-78

reverse address resolution 35-9

routed ports 35-5

static routing 35-3

steps to configure 35-5

subnet mask 35-7

subnet zero 35-7

supernet 35-8

UDP 35-16

with SVIs 35-5

See also BGP

See also EIGRP

See also OSPF

See also RIP

IPv4 ACLs

applying to interfaces 32-20

extended, creating 32-11

named 32-15

standard, creating 32-10

IPv4 and IPv6

configuring on an interface 36-13

differences 36-1

dual protocol stacks 36-5

IPv6

- addresses [36-2](#)
 - address formats [36-2](#)
 - advantages [36-2](#)
 - and switch stacks [36-7](#)
 - applications [36-5](#)
 - assigning address [36-11](#)
 - autoconfiguration [36-5](#)
 - CEFv6 [36-15](#)
 - configuring static routes [36-16](#)
 - default configuration [36-11](#)
 - defined [36-1](#)
 - enabling [36-11](#)
 - feature limitations [36-7](#)
 - features not supported [36-6](#)
 - ICMP [36-4](#)
 - ICMP rate limiting [36-15](#)
 - monitoring [36-22](#)
 - OSPF [36-20](#)
 - path MTU discovery [36-4](#)
 - reasons for [36-1](#)
 - RIP [36-18](#)
 - SDM templates [8-2, 36-8](#)
 - stack master functions [36-8](#)
 - supported features [36-3](#)
 - switch limitations [36-7](#)
- IRDP
- configuring [35-13](#)
 - definition [35-13](#)
 - support for [1-10](#)
- ISL
- and IPv6 [36-3](#)
 - and trunk ports [11-3](#)
 - encapsulation [1-7, 13-16](#)
 - trunking with IEEE 802.1 tunneling [17-5](#)
- isolated port [16-2](#)
- isolated VLANs [16-2, 16-3](#)

J

- join messages, IGMP [24-3](#)

K

KDC

- described [9-32](#)
- See also Kerberos

- keepalive messages [18-2](#)

Kerberos

- authenticating to
 - boundary switch [9-35](#)
 - KDC [9-35](#)
 - network services [9-35](#)
- configuration examples [9-32](#)
- configuring [9-36](#)
- credentials [9-32](#)
- cryptographic software image [9-32](#)
- described [9-32](#)
- KDC [9-32](#)
- operation [9-34](#)
- realm [9-33](#)
- server [9-33](#)
- support for [1-8](#)
- switch as trusted third party [9-32](#)
- terms [9-33](#)
- TGT [9-34](#)
- tickets [9-32](#)

key distribution center

- See KDC

L

- l2protocol-tunnel command [17-13](#)

LACP

- Layer 2 protocol tunneling [17-9](#)
- See EtherChannel

- Layer 2 frames, classification with CoS [33-2](#)

Layer 2 interfaces, default configuration [11-15](#)

Layer 2 protocol tunneling

configuring [17-10](#)

configuring for EtherChannels [17-14](#)

default configuration [17-11](#)

defined [17-8](#)

guidelines [17-11](#)

Layer 2 traceroute

and ARP [41-17](#)

and CDP [41-16](#)

broadcast traffic [41-16](#)

described [41-16](#)

IP addresses and subnets [41-17](#)

MAC addresses and VLANs [41-16](#)

multicast traffic [41-16](#)

multiple devices on a port [41-17](#)

unicast traffic [41-16](#)

usage guidelines [41-16](#)

Layer 3 features [1-10](#)

Layer 3 interfaces

assigning IP addresses to [35-7](#)

assigning IPv4 and IPv6 addresses to [36-13](#)

assigning IPv6 addresses to [36-12](#)

changing from Layer 2 mode [35-7](#)

types of [35-5](#)

Layer 3 packets, classification methods [33-2](#)

LDAP [4-2](#)

LEDs, switch

See hardware installation guide

lightweight directory access protocol

See LDAP

line configuration mode [2-3](#)

Link Aggregation Control Protocol

See EtherChannel

Link Failure

detecting unidirectional [19-8](#)

link local unicast addresses [36-3](#)

link redundancy

See Flex Links

links, unidirectional [27-1](#)

link state advertisements (LSAs) [35-30](#)

link-state protocols [35-3](#)

load balancing [37-3](#)

local SPAN [28-2](#)

logging messages, ACL [32-9](#)

login authentication

with RADIUS [9-23](#)

with TACACS+ [9-14](#)

login banners [7-17](#)

log messages

See system message logging

Long-Reach Ethernet (LRE) technology [1-16, 1-23](#)

loop guard

described [20-11](#)

enabling [20-18](#)

support for [1-6](#)

M

MAC addresses

aging time [7-21](#)

and VLAN association [7-20](#)

building the address table [7-20](#)

default configuration [7-21](#)

discovering [7-27](#)

displaying [7-26](#)

displaying in the IP source binding table [22-18](#)

dynamic

learning [7-20](#)

removing [7-22](#)

in ACLs [32-27](#)

IP address association [35-9](#)

static

adding [7-25](#)

allowing [7-26](#)

characteristics of [7-24](#)

dropping [7-26](#)

removing [7-25](#)

- MAC address notification, support for [1-11](#)
- MAC address-to-VLAN mapping [13-28](#)
- MAC extended access lists
 - applying to Layer 2 interfaces [32-29](#)
 - configuring for QoS [33-45](#)
 - creating [32-27](#)
 - defined [32-27](#)
 - for QoS classification [33-5](#)
- macros
 - See Smartports macros
- magic packet [10-10](#)
- manageability features [1-5](#)
- management access
 - in-band
 - browser session [1-5](#)
 - CLI session [1-5](#)
 - device manager [1-5](#)
 - SNMP [1-5](#)
 - out-of-band console port connection [1-6](#)
- management options
 - CLI [2-1](#)
 - clustering [1-3](#)
 - CNS [4-1](#)
 - Network Assistant [1-2](#)
 - overview [1-4](#)
 - switch stacks [1-3](#)
- mapping tables for QoS
 - configuring
 - CoS-to-DSCP [33-61](#)
 - DSCP [33-61](#)
 - DSCP-to-CoS [33-64](#)
 - DSCP-to-DSCP-mutation [33-65](#)
 - IP-precedence-to-DSCP [33-62](#)
 - policed-DSCP [33-63](#)
 - described [33-12](#)
- marking
 - action in policy map [33-48](#)
 - action with aggregate policers [33-59](#)
 - described [33-4, 33-8](#)
- matching, IPv4 ACLs [32-8](#)
- maximum aging time
 - MSTP [19-24](#)
 - STP [18-23](#)
- maximum hop count, MSTP [19-24](#)
- maximum-paths command [35-49, 35-75](#)
- membership mode, VLAN port [13-3](#)
- member switch
 - defined [6-2](#)
 - managing [6-4](#)
 - recovering from lost connectivity [41-12](#)
 - requirements [6-3](#)
 - See also candidate switch, cluster standby group, and standby command switch
- messages
 - to users through banners [7-17](#)
- messages, to users through banners [7-17](#)
- metrics, in BGP [35-50](#)
- metric translations, between routing protocols [35-81](#)
- metro tags [17-2](#)
- MHSRP [37-3](#)
- MIBs
 - accessing files with FTP [A-3](#)
 - location of files [A-3](#)
 - overview [31-1](#)
 - SNMP interaction with [31-4](#)
 - supported [A-1](#)
- mini-point-of-presence
 - See POP
- mirroring traffic for analysis [28-1](#)
- mismatches, autonegotiation [41-12](#)
- module number [11-10](#)
- monitoring
 - access groups [32-41](#)
 - BGP [35-62](#)
 - cables for unidirectional links [27-1](#)
 - CDP [26-5](#)
 - CEF [35-74](#)
 - EIGRP [35-40](#)

- monitoring (continued)
 - fallback bridging [40-11](#)
 - features [1-11](#)
 - Flex Links [21-3](#)
 - HSRP [37-11](#)
 - IEEE 802.1Q tunneling [17-18](#)
 - IGMP
 - filters [24-26](#)
 - snooping [24-13](#)
 - interfaces [11-26](#)
 - IP
 - address tables [35-18](#)
 - multicast routing [38-50](#)
 - routes [35-88](#)
 - IPv4 ACL configuration [32-41](#)
 - IPv6 [36-22](#)
 - Layer 2 protocol tunneling [17-18](#)
 - MSDP peers [39-19](#)
 - multicast router interfaces [24-14](#)
 - multi-VRF CE [35-73](#)
 - MVR [24-21](#)
 - network traffic for analysis with probe [28-2](#)
 - OSPF [35-34](#)
 - port
 - blocking [25-17](#)
 - protection [25-17](#)
 - private VLANs [16-15](#)
 - RP mapping information [38-23](#)
 - SFP status [11-26, 41-14](#)
 - source-active messages [39-19](#)
 - speed and duplex mode [11-18](#)
 - traffic flowing among switches [29-1](#)
 - traffic suppression [25-17](#)
 - tunneling [17-18](#)
 - VLAN
 - filters [32-41](#)
 - maps [32-41](#)
 - VLANs [13-15](#)
- monitoring (continued)
 - VMPS [13-32](#)
 - VTP [14-16](#)
- MSDP
 - benefits of [39-3](#)
 - clearing MSDP connections and statistics [39-19](#)
 - controlling source information
 - forwarded by switch [39-12](#)
 - originated by switch [39-8](#)
 - received by switch [39-14](#)
 - default configuration [39-4](#)
 - dense-mode regions
 - sending SA messages to [39-17](#)
 - specifying the originating address [39-18](#)
 - filtering
 - incoming SA messages [39-14](#)
 - SA messages to a peer [39-12](#)
 - SA requests from a peer [39-11](#)
 - join latency, defined [39-6](#)
 - meshed groups
 - configuring [39-16](#)
 - defined [39-16](#)
 - originating address, changing [39-18](#)
 - overview [39-1](#)
 - peer-RPF flooding [39-2](#)
 - peers
 - configuring a default [39-4](#)
 - monitoring [39-19](#)
 - peering relationship, overview [39-1](#)
 - requesting source information from [39-8](#)
 - shutting down [39-16](#)

MSDP (continued)

source-active messages

- caching 39-6
- clearing cache entries 39-19
- defined 39-2
- filtering from a peer 39-11
- filtering incoming 39-14
- filtering to a peer 39-12
- limiting data with TTL 39-14
- monitoring 39-19
- restricting advertised sources 39-9

support for 1-10

MSTP

boundary ports

- configuration guidelines 19-16
- described 19-6

BPDU filtering

- described 20-3
- enabling 20-14

BPDU guard

- described 20-3
- enabling 20-13

CIST, described 19-3

CIST regional root 19-3

CIST root 19-5

configuration guidelines 19-15, 20-12

configuring

- forward-delay time 19-23
- hello time 19-22
- link type for rapid convergence 19-25
- maximum aging time 19-24
- maximum hop count 19-24
- MST region 19-16
- neighbor type 19-25
- path cost 19-21
- port priority 19-20
- root switch 19-17
- secondary root switch 19-19
- switch priority 19-22

MSTP (continued)

CST

- defined 19-3
- operations between regions 19-4

default configuration 19-15

default optional feature configuration 20-12

displaying status 19-26

enabling the mode 19-16

EtherChannel guard

- described 20-10
- enabling 20-17

extended system ID

- effects on root switch 19-17
- effects on secondary root switch 19-19
- unexpected behavior 19-18

IEEE 802.1s

- implementation 19-6
- port role naming change 19-7
- terminology 19-5

instances supported 18-10

interface state, blocking to forwarding 20-2

interoperability and compatibility among modes 18-11

interoperability with IEEE 802.1D

- described 19-9
- restarting migration process 19-26

IST

- defined 19-3
- master 19-3
- operations within a region 19-3

loop guard

- described 20-11
- enabling 20-18

mapping VLANs to MST instance 19-16

- MSTP (continued)
 - MST region
 - CIST [19-3](#)
 - configuring [19-16](#)
 - described [19-2](#)
 - hop-count mechanism [19-5](#)
 - IST [19-3](#)
 - supported spanning-tree instances [19-2](#)
 - optional features supported [1-6](#)
 - overview [19-2](#)
 - Port Fast
 - described [20-2](#)
 - enabling [20-12](#)
 - preventing root switch selection [20-10](#)
 - root guard
 - described [20-10](#)
 - enabling [20-17](#)
 - root switch
 - configuring [19-18](#)
 - effects of extended system ID [19-17](#)
 - unexpected behavior [19-18](#)
 - shutdown Port Fast-enabled port [20-3](#)
 - stack changes, effects of [19-8](#)
 - status, displaying [19-26](#)
- multicast groups
 - Immediate Leave [24-5](#)
 - joining [24-3](#)
 - leaving [24-5](#)
 - static joins [24-10](#)
- multicast packets
 - ACLs on [32-40](#)
 - blocking [25-7](#)
- multicast router interfaces, monitoring [24-14](#)
- multicast router ports, adding [24-9](#)
- Multicast Source Discovery Protocol
 - See MSDP
- multicast storm [25-1](#)
- multicast storm-control command [25-4](#)
- multicast television application [24-15](#)
- multicast VLAN [24-15](#)
- Multicast VLAN Registration
 - See MVR
- Multiple HSRP
 - See MHSRP
- multiple VPN routing/forwarding in customer edge devices
 - See multi-VRF CE
- multi-VRF CE
 - configuration example [35-69](#)
 - configuration guidelines [35-66](#)
 - configuring [35-65](#)
 - default configuration [35-65](#)
 - defined [35-63](#)
 - displaying [35-73](#)
 - monitoring [35-73](#)
 - network components [35-65](#)
 - packet-forwarding process [35-65](#)
 - support for [1-10](#)
- MVR
 - and address aliasing [24-18](#)
 - and IGMPv3 [24-18](#)
 - configuration guidelines [24-17](#)
 - configuring interfaces [24-19](#)
 - default configuration [24-17](#)
 - described [24-15](#)
 - example application [24-15](#)
 - in the switch stack [24-17](#)
 - modes [24-19](#)
 - monitoring [24-21](#)
 - multicast television application [24-15](#)
 - setting global parameters [24-18](#)
 - support for [1-4](#)

N

- named IPv4 ACLs [32-15](#)
- NameSpace Mapper
 - See NSM
- native VLAN
 - and IEEE 802.1Q tunneling [17-4](#)
 - configuring [13-23](#)
 - default [13-23](#)
- neighbor discovery/recovery, EIGRP [35-35](#)
- neighbors, BGP [35-56](#)
- Network Assistant
 - benefits [1-2](#)
 - described [1-4](#)
 - downloading image files [1-2](#)
 - guide mode [1-2](#)
 - management options [1-2](#)
 - managing switch stacks [5-2, 5-15](#)
 - requirements [xl](#)
 - upgrading a switch [B-19](#)
 - wizards [1-2](#)
- network configuration examples
 - cost-effective wiring closet [1-16](#)
 - high-performance wiring closet [1-16](#)
 - increasing network performance [1-14](#)
 - large network [1-21](#)
 - long-distance, high-bandwidth transport [1-24](#)
 - multidwelling network [1-23](#)
 - providing network services [1-15](#)
 - redundant Gigabit backbone [1-17](#)
 - server aggregation and Linux server cluster [1-18](#)
 - small to medium-sized network [1-19](#)
- network design
 - performance [1-15](#)
 - services [1-15](#)
- network management
 - CDP [26-1](#)
 - RMON [29-1](#)
 - SNMP [31-1](#)
- Network Time Protocol
 - See NTP
- no commands [2-4](#)
- nonhierarchical policy maps
 - configuration guidelines [33-33](#)
 - configuring [33-48](#)
 - described [33-9](#)
- non-IP traffic filtering [32-27](#)
- nontrunking mode [13-18](#)
- normal-range VLANs [13-4](#)
 - configuration guidelines [13-6](#)
 - configuration modes [13-7](#)
 - configuring [13-4](#)
 - defined [13-1](#)
- no switchport command [11-4](#)
- note, described [xl](#)
- not-so-stubby areas
 - See NSSA
- NSM [4-3](#)
- NSSA, OSPF [35-30](#)
- NTP
 - associations
 - authenticating [7-5](#)
 - defined [7-2](#)
 - enabling broadcast messages [7-7](#)
 - peer [7-6](#)
 - server [7-6](#)
 - default configuration [7-4](#)
 - displaying the configuration [7-11](#)
 - overview [7-2](#)
 - restricting access
 - creating an access group [7-9](#)
 - disabling NTP services per interface [7-10](#)
 - source IP address, configuring [7-10](#)
 - stratum [7-2](#)
 - support for [1-5](#)
 - synchronizing devices [7-6](#)

NTP (continued)

time

services 7-2

synchronizing 7-2

O

offline configuration for switch stacks 5-7

Open Shortest Path First

See OSPF

optimizing system resources 8-1

options, management 1-4

OSPF

area parameters, configuring 35-30

configuring 35-28

default configuration

metrics 35-31

route 35-31

settings 35-26

described 35-25

for IPv6 36-20

interface parameters, configuring 35-28

LSA group pacing 35-33

monitoring 35-34

router IDs 35-33

route summarization 35-31

support for 1-10

virtual links 35-31

out-of-profile markdown 1-9

P

packet modification, with QoS 33-19

PAGP

Layer 2 protocol tunneling 17-9

See EtherChannel

parallel paths, in routing tables 35-75

passive interfaces

configuring 35-84

OSPF 35-31

passwords

default configuration 9-2

disabling recovery of 9-5

encrypting 9-3

for security 1-7

overview 9-1

recovery of 41-3

setting

enable 9-3

enable secret 9-3

Telnet 9-6

with usernames 9-6

VTP domain 14-8

path cost

MSTP 19-21

STP 18-19

path MTU discovery 36-4

PBR

defined 35-81

enabling 35-83

fast-switched policy-based routing 35-84

local policy-based routing 35-84

peers, BGP 35-56

performance, network design 1-14

performance features 1-3

persistent self-signed certificate 9-43

per-VLAN spanning-tree plus

See PVST+

PE to CE routing, configuring 35-68

physical ports 11-2

PIM

default configuration 38-9

dense mode

overview 38-4

rendezvous point (RP), described 38-4

RPF lookups 38-7

PIM (continued)

- displaying neighbors [38-51](#)
 - enabling a mode [38-12](#)
 - overview [38-3](#)
 - router-query message interval, modifying [38-26](#)
 - shared tree and source tree, overview [38-24](#)
 - shortest path tree, delaying the use of [38-25](#)
 - sparse mode
 - join messages and shared tree [38-4](#)
 - overview [38-4](#)
 - prune messages [38-5](#)
 - RPF lookups [38-7](#)
 - support for [1-10](#)
 - versions
 - interoperability [38-9](#)
 - troubleshooting interoperability problems [38-23](#)
 - v2 improvements [38-4](#)
- PIM-DVMRP, as snooping method [24-8](#)
- ping
- character output description [41-15](#)
 - executing [41-15](#)
 - overview [41-14](#)
- PoE
- auto mode [11-8](#)
 - CDP with power consumption, described [11-6](#)
 - CDP with power negotiation, described [11-6](#)
 - Cisco intelligent power management [11-6](#)
 - configuring [11-21](#)
 - devices supported [11-6](#)
 - high-power devices operating in low-power mode [11-6](#)
 - IEEE power classification levels [11-7](#)
 - powered-device detection and initial power allocation [11-7](#)
 - power management modes [11-8](#)
 - power negotiation extensions to CDP [11-6](#)
 - standards supported [11-6](#)
 - static mode [11-8](#)
 - supported watts per port [11-6](#)
 - troubleshooting [41-13](#)

- policed-DSCP map for QoS [33-63](#)
- policers
 - configuring
 - for each matched traffic class [33-48](#)
 - for more than one traffic class [33-59](#)
 - described [33-4](#)
 - displaying [33-79](#)
 - number of [33-34](#)
 - types of [33-9](#)
- policing
 - described [33-4](#)
 - hierarchical
 - See hierarchical policy maps
 - token-bucket algorithm [33-9](#)
- policy-based routing
 - See PBR
- policy maps for QoS
 - characteristics of [33-48](#)
 - described [33-7](#)
 - displaying [33-80](#)
 - hierarchical [33-8](#)
 - hierarchical on SVIs
 - configuration guidelines [33-33](#)
 - configuring [33-52](#)
 - described [33-11](#)
 - nonhierarchical on physical ports
 - configuration guidelines [33-33](#)
 - configuring [33-48](#)
 - described [33-9](#)
- POP [1-23](#)
- port ACLs
 - defined [32-2](#)
 - types of [32-3](#)
- Port Aggregation Protocol
 - See EtherChannel

- port-based authentication
 - accounting [10-5](#)
 - authentication server
 - defined [10-2](#)
 - RADIUS server [10-2](#)
 - client, defined [10-2](#)
 - configuration guidelines [10-14](#)
 - configuring
 - 802.1x authentication [10-16](#)
 - guest VLAN [10-23](#)
 - host mode [10-23](#)
 - manual re-authentication of a client [10-20](#)
 - periodic re-authentication [10-19](#)
 - quiet period [10-20](#)
 - RADIUS server [10-18](#)
 - RADIUS server parameters on the switch [10-17](#)
 - switch-to-client frame-retransmission number [10-21](#), [10-22](#)
 - switch-to-client retransmission time [10-21](#)
 - default configuration [10-13](#)
 - described [10-1](#)
 - device roles [10-2](#)
 - displaying statistics [10-26](#)
 - EAPOL-start frame [10-3](#)
 - EAP-request/identity frame [10-3](#)
 - EAP-response/identity frame [10-3](#)
 - encapsulation [10-3](#)
 - guest VLAN
 - configuration guidelines [10-10](#)
 - described [10-10](#)
 - host mode [10-6](#)
 - initiation and message exchange [10-3](#)
 - magic packet [10-10](#)
 - method lists [10-16](#)
 - multiple-hosts mode, described [10-6](#)
- port-based authentication (continued)
 - per-user ACLs
 - AAA authorization [10-16](#)
 - configuration tasks [10-12](#)
 - described [10-11](#)
 - RADIUS server attributes [10-11](#)
 - ports
 - authorization state and dot1x port-control command [10-4](#)
 - authorized and unauthorized [10-4](#)
 - voice VLAN [10-8](#)
 - port security
 - and voice VLAN [10-7](#)
 - described [10-7](#)
 - interactions [10-7](#)
 - multiple-hosts mode [10-6](#)
 - resetting to default values [10-25](#)
 - stack changes, effects of [10-12](#)
 - statistics, displaying [10-26](#)
 - switch
 - as proxy [10-2](#)
 - RADIUS client [10-3](#)
 - upgrading from a previous release [10-15](#), [33-26](#)
 - VLAN assignment
 - AAA authorization [10-16](#)
 - characteristics [10-9](#)
 - configuration tasks [10-9](#)
 - described [10-8](#)
 - voice VLAN
 - described [10-8](#)
 - PVID [10-8](#)
 - VVID [10-8](#)
 - wake-on-LAN, described [10-10](#)
- port blocking [1-4](#), [25-6](#)
- port-channel
 - See EtherChannel

- Port Fast
 - described 20-2
 - enabling 20-12
 - mode, spanning tree 13-29
 - support for 1-6
- port membership modes, VLAN 13-3
- port priority
 - MSTP 19-20
 - STP 18-18
- ports
 - 10-Gigabit Ethernet module 11-6
 - access 11-3
 - blocking 25-6
 - dynamic access 13-3
 - IEEE 802.1Q tunnel 13-4
 - protected 25-5
 - routed 11-4
 - secure 25-7
 - static-access 13-3, 13-11
 - switch 11-2
 - trunks 13-3, 13-16
 - VLAN assignments 13-11
- port security
 - aging 25-15
 - and QoS trusted boundary 33-38
 - and stacking 25-16
 - configuring 25-12
 - default configuration 25-10
 - described 25-7
 - displaying 25-17
 - on trunk ports 25-13
 - sticky learning 25-8
 - violations 25-9
 - with other features 25-10
- port-shutdown response, VMPS 13-28
- Power over Ethernet
 - See PoE
- preferential treatment of traffic
 - See QoS
- prefix lists, BGP 35-54
- preventing unauthorized access 9-1
- primary links 21-1
- primary VLANs 16-1, 16-3
- priority
 - HSRP 37-7
 - overriding CoS 15-6
 - trusting CoS 15-6
- private VLAN edge ports
 - See protected ports
- private VLANs
 - across multiple switches 16-4
 - and SDM template 16-4
 - and SVIs 16-5
 - and switch stacks 16-5
 - benefits of 16-1
 - community ports 16-2
 - community VLANs 16-2, 16-3
 - configuration guidelines 16-7, 16-8
 - configuration tasks 16-6
 - configuring 16-10
 - default configuration 16-6
 - end station access to 16-3
 - IP addressing 16-3
 - isolated port 16-2
 - isolated VLANs 16-2, 16-3
 - mapping 16-14
 - monitoring 16-15
 - ports
 - community 16-2
 - configuration guidelines 16-8
 - configuring host ports 16-11
 - configuring promiscuous ports 16-13
 - described 13-4
 - isolated 16-2
 - promiscuous 16-2
 - primary VLANs 16-1, 16-3
 - promiscuous ports 16-2
 - secondary VLANs 16-2

- private VLANs (continued)
 - subdomains 16-1
 - traffic in 16-5
 - privileged EXEC mode 2-2
 - privilege levels
 - changing the default for lines 9-9
 - command switch 6-4
 - exiting 9-9
 - logging into 9-9
 - mapping on member switches 6-4
 - overview 9-2, 9-7
 - setting a command with 9-8
 - promiscuous ports
 - configuring 16-13
 - defined 16-2
 - protected ports 1-7, 25-5
 - protocol-dependent modules, EIGRP 35-35
 - Protocol-Independent Multicast Protocol
 - See PIM
 - provider edge devices 35-64
 - provisioning new members for a switch stack 5-7
 - proxy ARP
 - configuring 35-12
 - definition 35-10
 - with IP routing disabled 35-12
 - pruning, VTP
 - disabling
 - in VTP domain 14-14
 - on a port 13-23
 - enabling
 - in VTP domain 14-14
 - on a port 13-23
 - examples 14-5
 - overview 14-4
 - pruning-eligible list
 - changing 13-23
 - for VTP pruning 14-5
 - VLANs 14-14
 - PVST+
 - described 18-10
 - IEEE 802.1Q trunking interoperability 18-11
 - instances supported 18-10
-
- Q
- QoS
 - and MQC commands 33-1
 - auto-QoS
 - categorizing traffic 33-20
 - configuration and defaults display 33-30
 - configuration guidelines 33-25
 - described 33-20
 - disabling 33-27
 - displaying generated commands 33-27
 - displaying the initial configuration 33-30
 - effects on running configuration 33-25
 - egress queue defaults 33-21
 - enabling for VoIP 33-27
 - example configuration 33-28
 - ingress queue defaults 33-21
 - list of generated commands 33-22
 - basic model 33-4
 - classification
 - class maps, described 33-7
 - defined 33-4
 - DSCP transparency, described 33-39
 - flowchart 33-6
 - forwarding treatment 33-3
 - in frames and packets 33-3
 - IP ACLs, described 33-5, 33-7
 - MAC ACLs, described 33-5, 33-7
 - options for IP traffic 33-5
 - options for non-IP traffic 33-5
 - policy maps, described 33-7
 - trust DSCP, described 33-5
 - trusted CoS, described 33-5
 - trust IP precedence, described 33-5

QoS (continued)

- class maps
 - configuring [33-46](#)
 - displaying [33-79](#)
- configuration guidelines
 - auto-QoS [33-25](#)
 - standard QoS [33-33](#)
- configuring
 - aggregate policers [33-59](#)
 - auto-QoS [33-20](#)
 - default port CoS value [33-37](#)
 - DSCP maps [33-61](#)
 - DSCP transparency [33-39](#)
 - DSCP trust states bordering another domain [33-40](#)
 - egress queue characteristics [33-72](#)
 - ingress queue characteristics [33-67](#)
 - IP extended ACLs [33-44](#)
 - IP standard ACLs [33-43](#)
 - MAC ACLs [33-45](#)
 - policy maps, hierarchical [33-52](#)
 - policy maps on physical ports [33-48](#)
 - port trust states within the domain [33-36](#)
 - trusted boundary [33-38](#)
- default auto configuration [33-20](#)
- default standard configuration [33-31](#)
- displaying statistics [33-79](#)
- DSCP transparency [33-39](#)
- egress queues
 - allocating buffer space [33-72](#)
 - buffer allocation scheme, described [33-18](#)
 - configuring shaped weights for SRR [33-76](#)
 - configuring shared weights for SRR [33-77](#)
 - described [33-4](#)
 - displaying the threshold map [33-75](#)
 - flowchart [33-17](#)
 - mapping DSCP or CoS values [33-74](#)
 - scheduling, described [33-4](#)
 - setting WTD thresholds [33-72](#)
 - WTD, described [33-19](#)

QoS (continued)

- enabling globally [33-35](#)
- flowcharts
 - classification [33-6](#)
 - egress queueing and scheduling [33-17](#)
 - ingress queueing and scheduling [33-15](#)
 - policing and marking [33-10](#)
- implicit deny [33-7](#)
- ingress queues
 - allocating bandwidth [33-70](#)
 - allocating buffer space [33-69](#)
 - buffer and bandwidth allocation, described [33-16](#)
 - configuring shared weights for SRR [33-70](#)
 - configuring the priority queue [33-71](#)
 - described [33-4](#)
 - displaying the threshold map [33-68](#)
 - flowchart [33-15](#)
 - mapping DSCP or CoS values [33-68](#)
 - priority queue, described [33-16](#)
 - scheduling, described [33-4](#)
 - setting WTD thresholds [33-68](#)
 - WTD, described [33-16](#)
- IP phones
 - automatic classification and queueing [33-20](#)
 - detection and trusted settings [33-20, 33-38](#)
- limiting bandwidth on egress interface [33-78](#)
- mapping tables
 - CoS-to-DSCP [33-61](#)
 - displaying [33-79](#)
 - DSCP-to-CoS [33-64](#)
 - DSCP-to-DSCP-mutation [33-65](#)
 - IP-precedence-to-DSCP [33-62](#)
 - policed-DSCP [33-63](#)
 - types of [33-12](#)
- marked-down actions [33-50, 33-56](#)
- marking, described [33-4, 33-8](#)
- overview [33-2](#)
- packet modification [33-19](#)

QoS (continued)

- policers
 - configuring 33-50, 33-56, 33-59
 - described 33-8
 - displaying 33-79
 - number of 33-34
 - types of 33-9
 - policies, attaching to an interface 33-9
 - policing
 - described 33-4, 33-8
 - token bucket algorithm 33-9
 - policy maps
 - characteristics of 33-48
 - displaying 33-80
 - hierarchical 33-8
 - hierarchical on SVIs 33-52
 - nonhierarchical on physical ports 33-48
 - QoS label, defined 33-4
 - queues
 - configuring egress characteristics 33-72
 - configuring ingress characteristics 33-67
 - high priority (expedite) 33-19, 33-78
 - location of 33-13
 - SRR, described 33-14
 - WTD, described 33-13
 - rewrites 33-19
 - support for 1-8
 - trust states
 - bordering another domain 33-40
 - described 33-5
 - trusted device 33-38
 - within the domain 33-36
- quality of service
 - See QoS

queries, IGMP 24-4

R

RADIUS

- attributes
 - vendor-proprietary 9-30
 - vendor-specific 9-29
 - configuring
 - accounting 9-28
 - authentication 9-23
 - authorization 9-27
 - communication, global 9-21, 9-29
 - communication, per-server 9-20, 9-21
 - multiple UDP ports 9-20
 - default configuration 9-20
 - defining AAA server groups 9-25
 - displaying the configuration 9-31
 - identifying the server 9-20
 - limiting the services to the user 9-27
 - method list, defined 9-20
 - operation of 9-19
 - overview 9-17
 - suggested network environments 9-18
 - support for 1-8
 - tracking services accessed by user 9-28
- range
 - macro 11-13
 - of interfaces 11-12
- rapid convergence 19-10
- rapid per-VLAN spanning-tree plus
 - See rapid PVST+
- rapid PVST+
 - described 18-10
 - IEEE 802.1Q trunking interoperability 18-11
 - instances supported 18-10
- Rapid Spanning Tree Protocol
 - See RSTP
- RARP 35-10

- rcommand command [6-4](#)
- RCP
 - configuration files
 - downloading [B-17](#)
 - overview [B-15](#)
 - preparing the server [B-16](#)
 - uploading [B-18](#)
 - image files
 - deleting old image [B-33](#)
 - downloading [B-31](#)
 - preparing the server [B-29](#)
 - uploading [B-33](#)
- reconfirmation interval, VMPS, changing [13-31](#)
- reconfirming dynamic VLAN membership [13-31](#)
- recovery procedures [41-1](#)
- redundancy
 - EtherChannel [34-2](#)
 - HSRP [37-1](#)
 - STP
 - backbone [18-8](#)
 - multidrop backbone [20-5](#)
 - path cost [13-26](#)
 - port priority [13-24](#)
- redundant links and UplinkFast [20-15](#)
- reliable transport protocol, EIGRP [35-35](#)
- reloading software [3-16](#)
- Remote Authentication Dial-In User Service
 - See RADIUS
- Remote Copy Protocol
 - See RCP
- Remote Network Monitoring
 - See RMON
- Remote SPAN
 - See RSPAN
- remote SPAN [28-3](#)
- report suppression, IGMP
 - described [24-6](#)
 - disabling [24-13](#)
- requirements
 - cluster [xli](#)
 - device manager [xl](#)
 - Network Assistant [xl](#)
- resequencing ACL entries [32-15](#)
- resets, in BGP [35-48](#)
- resetting a UDLD-shutdown interface [27-6](#)
- restricting access
 - NTP services [7-8](#)
 - overview [9-1](#)
 - passwords and privilege levels [9-2](#)
 - RADIUS [9-17](#)
 - TACACS+ [9-9](#)
- retry count, VMPS, changing [13-32](#)
- reverse address resolution [35-9](#)
- Reverse Address Resolution Protocol
 - See RARP
- RFC
 - 1058, RIP [35-20](#)
 - 1112, IP multicast and IGMP [24-2](#)
 - 1157, SNMPv1 [31-2](#)
 - 1163, BGP [35-41](#)
 - 1166, IP addresses [35-6](#)
 - 1253, OSPF [35-25](#)
 - 1267, BGP [35-41](#)
 - 1305, NTP [7-2](#)
 - 1587, NSSAs [35-25](#)
 - 1757, RMON [29-2](#)
 - 1771, BGP [35-41](#)
 - 1901, SNMPv2C [31-2](#)
 - 1902 to 1907, SNMPv2 [31-2](#)
 - 2236, IP multicast and IGMP [24-2](#)
 - 2273-2275, SNMPv3 [31-2](#)
- RIP
 - advertisements [35-20](#)
 - authentication [35-23](#)
 - configuring [35-21](#)
 - default configuration [35-21](#)
 - described [35-20](#)

- RIP (continued)
 - for IPv6 36-18
 - hop counts 35-20
 - split horizon 35-23
 - summary addresses 35-23
 - support for 1-10
- RMON
 - default configuration 29-3
 - displaying status 29-6
 - enabling alarms and events 29-3
 - groups supported 29-2
 - overview 29-1
 - statistics
 - collecting group Ethernet 29-6
 - collecting group history 29-5
 - support for 1-11
- root guard
 - described 20-10
 - enabling 20-17
 - support for 1-6
- root switch
 - MSTP 19-17
 - STP 18-16
- route calculation timers, OSPF 35-31
- route dampening, BGP 35-61
- routed packets, ACLs on 32-39
- routed ports
 - configuring 35-5
 - defined 11-4
 - IP addresses on 11-23, 35-5
- route-map command 35-83
- route maps
 - BGP 35-51
 - policy-based routing 35-81
- router ACLs
 - defined 32-2
 - types of 32-4
- route reflectors, BGP 35-59
- router ID, OSPF 35-33
- route selection, BGP 35-49
- route summarization, OSPF 35-31
- route targets, VPN 35-65
- routing
 - default 35-3
 - dynamic 35-3
 - redistribution of information 35-78
 - static 35-3
- routing domain confederation, BGP 35-59
- Routing Information Protocol
 - See RIP
- routing protocol administrative distances 35-76
- RSPAN 28-3
 - and stack changes 28-10
 - characteristics 28-9
 - configuration guidelines 28-17
 - default configuration 28-11
 - destination ports 28-7
 - displaying status 28-24
 - in a switch stack 28-2
 - interaction with other features 28-9
 - monitored ports 28-6
 - monitoring ports 28-7
 - overview 1-11, 28-1
 - received traffic 28-5
 - session limits 28-11
 - sessions
 - creating 28-18
 - defined 28-4
 - limiting source traffic to specific VLANs 28-23
 - specifying monitored ports 28-18
 - with ingress traffic enabled 28-21
 - source ports 28-6
 - transmitted traffic 28-6
 - VLAN-based 28-7

RSTP

- active topology [19-10](#)
- BPDU
 - format [19-12](#)
 - processing [19-13](#)
- designated port, defined [19-9](#)
- designated switch, defined [19-9](#)
- interoperability with IEEE 802.1D
 - described [19-9](#)
 - restarting migration process [19-26](#)
 - topology changes [19-13](#)
- overview [19-9](#)
- port roles
 - described [19-9](#)
 - synchronized [19-11](#)
- proposal-agreement handshake process [19-10](#)
- rapid convergence
 - cross-stack rapid convergence [19-11](#)
 - described [19-10](#)
 - edge ports and Port Fast [19-10](#)
 - point-to-point links [19-10, 19-25](#)
 - root ports [19-10](#)
- root port, defined [19-9](#)
- See also MSTP
- running configuration, saving [3-10](#)

S

- scheduled reloads [3-16](#)

SDM

- described [8-1](#)
- switch stack consideration [5-9](#)
- templates
 - configuring [8-6](#)
 - number of [8-1](#)
- SDM mismatch mode [5-9, 8-4](#)

SDM template

- aggregator [8-1](#)
- configuration guidelines [8-5](#)
- configuring [8-5](#)
- desktop [8-1](#)
- dual IPv4 and IPv6 [8-2](#)
- types of [8-1](#)
- secondary VLANs [16-2](#)
- secure HTTP client
 - configuring [9-47](#)
 - displaying [9-48](#)
- secure HTTP server
 - configuring [9-46](#)
 - displaying [9-48](#)
- secure MAC addresses
 - and switch stacks [25-17](#)
 - deleting [25-14](#)
 - maximum number of [25-9](#)
 - types of [25-8](#)
- secure ports
 - and switch stacks [25-16](#)
 - configuring [25-7](#)
- secure remote connections [9-38](#)
- Secure Shell
 - See SSH
- Secure Socket Layer
 - See SSL
- security, port [25-7](#)
- security features [1-7](#)
- sequence numbers in log messages [31-8](#)
- server mode, VTP [14-3](#)
- service-provider network, MSTP and RSTP [19-1](#)
- service-provider networks
 - and customer VLANs [17-2](#)
 - and IEEE 802.1Q tunneling [17-1](#)
 - Layer 2 protocols across [17-8](#)
 - Layer 2 protocol tunneling for EtherChannels [17-9](#)
- set-request operation [31-4](#)

- setup program
 - failed command switch replacement [41-11](#)
 - replacing failed command switch [41-9](#)
- severity levels, defining in system messages [31-9](#)
- SFPs
 - monitoring status of [11-26, 41-14](#)
 - numbering of [11-11](#)
 - security and identification [41-13](#)
 - status, displaying [41-14](#)
- shaped round robin
 - See SRR
- show access-lists hw-summary command [32-22](#)
- show and more command output, filtering [2-10](#)
- show cdp traffic command [26-5](#)
- show cluster members command [6-4](#)
- show configuration command [11-22](#)
- show forward command [41-22](#)
- show interfaces command [11-18, 11-22](#)
- show l2protocol command [17-14, 17-16](#)
- show platform forward command [41-22](#)
- show running-config command
 - displaying ACLs [32-20, 32-21, 32-32, 32-34](#)
 - interface description in [11-22](#)
- shutdown command on interfaces [11-27](#)
- shutdown threshold for Layer 2 protocol packets [17-11](#)
- Simple Network Management Protocol
 - See SNMP
- small form-factor pluggable modules
 - See SFPs
- Smartports macros
 - applying Cisco-default macros [12-6](#)
 - applying global parameter values [12-5, 12-6](#)
 - applying macros [12-5](#)
 - applying parameter values [12-5, 12-7](#)
 - configuration guidelines [12-3](#)
 - creating [12-4](#)
 - default configuration [12-2](#)
 - defined [12-1](#)
 - displaying [12-8](#)
- Smartports macros (continued)
 - tracing [12-3](#)
 - website [12-2](#)
- SNAP [26-1](#)
- SNMP
 - accessing MIB variables with [31-4](#)
 - agent
 - described [31-4](#)
 - disabling [31-8](#)
 - authentication level [31-10](#)
 - community strings
 - configuring [31-8](#)
 - for cluster switches [31-4](#)
 - overview [31-4](#)
 - configuration examples [31-15](#)
 - default configuration [31-6](#)
 - engine ID [31-7](#)
 - groups [31-7, 31-9](#)
 - host [31-7](#)
 - ifIndex values [31-5](#)
 - in-band management [1-5](#)
 - informs
 - and trap keyword [31-11](#)
 - described [31-5](#)
 - differences from traps [31-5](#)
 - disabling [31-14](#)
 - enabling [31-14](#)
 - limiting access by TFTP servers [31-15](#)
 - limiting system log messages to NMS [31-10](#)
 - manager functions [1-5, 31-3](#)
 - managing clusters with [6-5](#)
 - MIBs
 - location of [A-3](#)
 - supported [A-1](#)
 - notifications [31-5](#)
 - overview [31-1, 31-4](#)
 - security levels [31-3](#)
 - status, displaying [31-16](#)
 - system contact and location [31-14](#)

SNMP (continued)

- trap manager, configuring [31-13](#)
- traps
 - described [31-3, 31-5](#)
 - differences from informs [31-5](#)
 - disabling [31-14](#)
 - enabling [31-11](#)
 - enabling MAC address notification [7-22](#)
 - overview [31-1, 31-4](#)
 - types of [31-11](#)
- users [31-7, 31-9](#)
- versions supported [31-2](#)
- SNMPv1 [31-2](#)
- SNMPv2C [31-2](#)
- SNMPv3 [31-2](#)
- snooping, IGMP [24-1](#)
- software compatibility
 - See stacks, switch
- software images
 - location in flash [B-20](#)
 - recovery procedures [41-2](#)
 - scheduling reloads [3-16](#)
 - tar file format, described [B-20](#)
 - See also downloading and uploading
- source addresses, in IPv4 ACLs [32-12](#)
- source-and-destination-IP address based forwarding, EtherChannel [34-8](#)
- source-and-destination MAC address forwarding, EtherChannel [34-8](#)
- source-IP address based forwarding, EtherChannel [34-8](#)
- source-MAC address forwarding, EtherChannel [34-8](#)
- SPAN
 - and stack changes [28-10](#)
 - configuration guidelines [28-11](#)
 - default configuration [28-11](#)
 - destination ports [28-7](#)
 - displaying status [28-24](#)
 - interaction with other features [28-9](#)
 - monitored ports [28-6](#)

SPAN (continued)

- monitoring ports [28-7](#)
- overview [1-11, 28-1](#)
- ports, restrictions [25-11](#)
- received traffic [28-5](#)
- session limits [28-11](#)
- sessions
 - configuring ingress forwarding [28-15, 28-22](#)
 - creating [28-12](#)
 - defined [28-4](#)
 - limiting source traffic to specific VLANs [28-16](#)
 - removing destination (monitoring) ports [28-14](#)
 - specifying monitored ports [28-12](#)
 - with ingress traffic enabled [28-14](#)
- source ports [28-6](#)
- transmitted traffic [28-6](#)
- VLAN-based [28-7](#)
- spanning tree and native VLANs [13-19](#)
- Spanning Tree Protocol
 - See STP
- SPAN traffic [28-5](#)
- speed, configuring on interfaces [11-17](#)
- split horizon, RIP [35-23](#)
- SRR
 - configuring
 - shaped weights on egress queues [33-76](#)
 - shared weights on egress queues [33-77](#)
 - shared weights on ingress queues [33-70](#)
 - described [33-14](#)
 - shaped mode [33-14](#)
 - shared mode [33-14](#)
 - support for [1-9](#)
- SSH
 - configuring [9-39](#)
 - cryptographic software image [9-37](#)
 - described [1-5, 9-38](#)
 - encryption methods [9-38](#)
 - switch stack considerations [5-16, 9-38](#)
 - user authentication methods, supported [9-38](#)

SSL

- configuration guidelines [9-44](#)
- configuring a secure HTTP client [9-47](#)
- configuring a secure HTTP server [9-46](#)
- cryptographic software image [9-42](#)
- described [9-41](#)
- monitoring [9-48](#)

stack, switch

- MAC address of [5-19](#)

stack changes

- effects on
 - IPv6 routing [36-7](#)

stack changes, effects on

- 802.1x port-based authentication [10-12](#)
- ACL configuration [32-7](#)
- CDP [26-2](#)
- cross-stack EtherChannel [34-12](#)
- EtherChannel [34-9](#)
- fallback bridging [40-3](#)
- HSRP [37-4](#)
- IGMP snooping [24-6](#)
- IP routing [35-4](#)
- MAC address tables [7-21](#)
- MSTP [19-8](#)
- multicast routing [38-8](#)
- MVR [24-15](#)
- port security [25-16](#)
- SDM template selection [8-4](#)
- SNMP [31-1](#)
- SPAN and RSPAN [28-10](#)
- STP [18-12](#)
- system message log [31-2](#)
- VLANs [13-6](#)
- VTP [14-6](#)

stack master

- bridge ID (MAC address) [5-5](#)
- defined [5-1](#)
- election [5-4](#)
- IPv6 [36-8](#)
- re-election [5-4](#)
- See also stacks, switch

stack member

- accessing CLI of specific member [5-22](#)
- configuring
 - member number [5-20](#)
 - priority value [5-21](#)
- defined [5-1](#)
- displaying information of [5-22](#)
- IPv6 [36-8](#)
- number [5-6](#)
- priority value [5-7](#)
- provisioning a new member [5-21](#)
- replacing [5-14](#)
- See also stacks, switch

stack member number [11-10](#)stack protocol version [5-10](#)

stacks, switch

- accessing CLI of specific member [5-22](#)
- assigning information
 - member number [5-20](#)
 - priority value [5-21](#)
 - provisioning a new member [5-21](#)
- auto-advise [5-11](#)
- auto-copy [5-11](#)
- auto-upgrade [5-11](#)
- benefits [1-2](#)
- bridge ID [5-5](#)
- CDP considerations [26-2](#)
- compatibility, software [5-10](#)
- configuration file [5-14](#)
- configuration scenarios [5-17](#)
- copying an image file from one member to another [B-34](#)
- default configuration [5-19](#)

stacks, switch (continued)

- description of 5-1
- displaying information of 5-22
- enabling persistent MAC address timer 5-19
- hardware compatibility and SDM mismatch mode 5-9
- HSRP considerations 37-4
- incompatible software and image upgrades 5-14, B-34
- IPv6 on 36-7
- MAC address considerations 7-21
- management connectivity 5-15
- managing 5-1
- membership 5-3
- merged 5-3
- MSTP instances supported 18-10
- multicast routing, stack master and member roles 38-8
- offline configuration
 - described 5-7
 - effects of adding a provisioned switch 5-7
 - effects of removing a provisioned switch 5-9
 - effects of replacing a provisioned switch 5-9
 - provisioned configuration, defined 5-7
 - provisioned switch, defined 5-7
 - provisioning a new member 5-21
- partitioned 5-3, 41-8
- provisioned switch
 - adding 5-7
 - removing 5-9
 - replacing 5-9
- replacing a failed member 5-14
- software compatibility 5-10
- software image version 5-10
- stack protocol version 5-10
- STP
 - bridge ID 18-3
 - instances supported 18-10
 - root port selection 18-3
 - stack root switch election 18-3

stacks, switch (continued)

- system messages
 - hostnames in the display 31-1
 - remotely monitoring 31-2
- system prompt consideration 7-14
- system-wide configuration considerations 5-15
- upgrading B-34
- version-mismatch (VM) mode
 - automatic upgrades with auto-upgrade 5-11
 - described 5-10
 - examples 5-12
 - manual upgrades with auto-advise 5-11
- See also stack master and stack member
- StackWise technology, Cisco 1-3
- See also stacks, switch
- standby command switch, requirements 6-2
- standby ip command 37-5
- standby links 21-1
- standby router 37-1
- standby timers, HSRP 37-9
- startup configuration
 - booting
 - manually 3-13
 - specific image 3-14
 - clearing B-19
 - configuration file
 - automatically downloading 3-12
 - specifying the filename 3-12
 - default boot configuration 3-12
- stateless autoconfiguration 36-5
- static access ports
 - assigning to VLAN 13-11
 - defined 11-3, 13-3
- static addresses
 - See addresses
- static IP routing 1-10
- static MAC addressing 1-7

- static routes
 - configuring 35-75
 - configuring for IPv6 36-16
- static routing 35-3
- static VLAN membership 13-2
- statistics
 - 802.1x 10-26
 - CDP 26-5
 - interface 11-26
 - IP multicast routing 38-51
 - OSPF 35-34
 - QoS ingress and egress 33-79
 - RMON group Ethernet 29-6
 - RMON group history 29-5
 - SNMP input and output 31-16
 - VTP 14-16
- sticky learning 25-8
- storm control
 - configuring 25-3
 - described 25-1
 - disabling 25-5
 - displaying 25-17
 - support for 1-4
 - thresholds 25-1
- STP
 - accelerating root port selection 20-4
 - BackboneFast
 - described 20-7
 - disabling 20-17
 - enabling 20-16
 - BPDU filtering
 - described 20-3
 - disabling 20-15
 - enabling 20-14
 - BPDU guard
 - described 20-3
 - disabling 20-14
 - enabling 20-13
 - BPDU message exchange 18-3
 - STP (continued)
 - configuration guidelines 18-13, 20-12
 - configuring
 - forward-delay time 18-23
 - hello time 18-22
 - maximum aging time 18-23
 - path cost 18-19
 - port priority 18-18
 - root switch 18-16
 - secondary root switch 18-17
 - spanning-tree mode 18-14
 - switch priority 18-21
 - counters, clearing 18-24
 - cross-stack UplinkFast
 - described 20-5
 - enabling 20-16
 - default configuration 18-13
 - default optional feature configuration 20-12
 - designated port, defined 18-4
 - designated switch, defined 18-4
 - detecting indirect link failures 20-8
 - disabling 18-15
 - displaying status 18-24
 - EtherChannel guard
 - described 20-10
 - disabling 20-17
 - enabling 20-17
 - extended system ID
 - effects on root switch 18-16
 - effects on the secondary root switch 18-17
 - overview 18-4
 - unexpected behavior 18-16
 - features supported 1-6
 - IEEE 802.1D and bridge ID 18-4
 - IEEE 802.1D and multicast addresses 18-9
 - IEEE 802.1t and VLAN identifier 18-4
 - inferior BPDU 18-3
 - instances supported 18-10
 - interface state, blocking to forwarding 20-2

STP (continued)

interface states

- blocking [18-6](#)
- disabled [18-7](#)
- forwarding [18-6, 18-7](#)
- learning [18-7](#)
- listening [18-7](#)
- overview [18-5](#)

interoperability and compatibility among modes [18-11](#)keepalive messages [18-2](#)Layer 2 protocol tunneling [17-8](#)limitations with IEEE 802.1Q trunks [18-11](#)

load sharing

- overview [13-24](#)
- using path costs [13-26](#)
- using port priorities [13-25](#)

loop guard

- described [20-11](#)
- enabling [20-18](#)

modes supported [18-10](#)multicast addresses, effect of [18-9](#)optional features supported [1-6](#)overview [18-2](#)path costs [13-26, 13-27](#)

Port Fast

- described [20-2](#)
- enabling [20-12](#)

port priorities [13-25](#)preventing root switch selection [20-10](#)protocols supported [18-10](#)redundant connectivity [18-8](#)

root guard

- described [20-10](#)
- enabling [20-17](#)

root port, defined [18-3](#)root port selection on a switch stack [18-3](#)

STP (continued)

root switch

- configuring [18-16](#)
- effects of extended system ID [18-4, 18-16](#)
- election [18-3](#)
- unexpected behavior [18-16](#)

shutdown Port Fast-enabled port [20-3](#)stack changes, effects of [18-12](#)status, displaying [18-24](#)superior BPDU [18-3](#)timers, described [18-22](#)

UplinkFast

- described [20-4](#)
- enabling [20-15](#)

VLAN-bridge [18-11](#)stratum, NTP [7-2](#)stub areas, OSPF [35-30](#)subdomains, private VLAN [16-1](#)subnet mask [35-7](#)subnet zero [35-7](#)success response, VMPS [13-28](#)summer time [7-13](#)SunNet Manager [1-5](#)supernet [35-8](#)

SVIs

- and IP unicast routing [35-5](#)
- and router ACLs [32-4](#)
- connecting VLANs [11-9](#)
- defined [11-5](#)
- routing between VLANs [13-2](#)

switch clustering technology [6-1](#)

See also clusters, switch

switch console port [1-6](#)

Switch Database Management

See SDM

switched packets, ACLs on [32-38](#)

Switched Port Analyzer

See SPAN

switched ports [11-2](#)

- switchport block multicast command 25-7
 - switchport block unicast command 25-7
 - switchport command 11-15
 - switchport mode dot1q-tunnel command 17-6
 - switchport protected command 25-6
 - switch priority
 - MSTP 19-22
 - STP 18-21
 - switch software features 1-1
 - switch virtual interface
 - See SVI
 - synchronization, BGP 35-45
 - syslog
 - See system message logging
 - system clock
 - configuring
 - daylight saving time 7-13
 - manually 7-11
 - summer time 7-13
 - time zones 7-12
 - displaying the time and date 7-12
 - overview 7-2
 - See also NTP
 - system message logging
 - default configuration 31-4
 - defining error message severity levels 31-9
 - disabling 31-4
 - displaying the configuration 31-13
 - enabling 31-5
 - facility keywords, described 31-13
 - level keywords, described 31-10
 - limiting messages 31-10
 - message format 31-2
 - overview 31-1
 - sequence numbers, enabling and disabling 31-8
 - setting the display destination device 31-5
 - stack changes, effects of 31-2
 - synchronizing log messages 31-6
 - syslog facility 1-11
 - system message logging (continued)
 - time stamps, enabling and disabling 31-8
 - UNIX syslog servers
 - configuring the daemon 31-12
 - configuring the logging facility 31-12
 - facilities supported 31-13
 - system MTU and IEEE 802.1Q tunneling 17-5
 - system name
 - default configuration 7-15
 - default setting 7-15
 - manual configuration 7-15
 - See also DNS
 - system prompt, default setting 7-14, 7-15
 - system resources, optimizing 8-1
-
- ## T
- TACACS+
 - accounting, defined 9-11
 - authentication, defined 9-11
 - authorization, defined 9-11
 - configuring
 - accounting 9-16
 - authentication key 9-13
 - authorization 9-16
 - login authentication 9-14
 - default configuration 9-13
 - displaying the configuration 9-17
 - identifying the server 9-13
 - limiting the services to the user 9-16
 - operation of 9-12
 - overview 9-10
 - support for 1-8
 - tracking services accessed by user 9-16
 - tagged packets
 - IEEE 802.1Q 17-3
 - Layer 2 protocol 17-8

- tar files
 - creating [B-6](#)
 - displaying the contents of [B-7](#)
 - extracting [B-7](#)
 - image file format [B-20](#)
- TDR [1-11](#)
- Telnet
 - accessing management interfaces [2-11](#)
 - number of connections [1-5](#)
 - setting a password [9-6](#)
- templates, SDM [8-1](#)
- temporary self-signed certificate [9-43](#)
- Terminal Access Controller Access Control System Plus
 - See TACACS+
- terminal lines, setting a password [9-6](#)
- TFTP
 - configuration files
 - downloading [B-11](#)
 - preparing the server [B-11](#)
 - uploading [B-12](#)
 - configuration files in base directory [3-6](#)
 - configuring for autoconfiguration [3-6](#)
 - image files
 - deleting [B-23](#)
 - downloading [B-22](#)
 - preparing the server [B-21](#)
 - uploading [B-24](#)
 - limiting access by servers [31-15](#)
- TFTP server [1-5](#)
- threshold, traffic level [25-2](#)
- time
 - See NTP and system clock
- Time Domain Reflector
 - See TDR
- time-range command [32-17](#)
- time ranges in ACLs [32-17](#)
- time stamps in log messages [31-8](#)
- time zones [7-12](#)
- Token Ring VLANs
 - support for [13-6](#)
 - VTP support [14-4](#)
- ToS [1-9](#)
- traceroute, Layer 2
 - and ARP [41-17](#)
 - and CDP [41-16](#)
 - broadcast traffic [41-16](#)
 - described [41-16](#)
 - IP addresses and subnets [41-17](#)
 - MAC addresses and VLANs [41-16](#)
 - multicast traffic [41-16](#)
 - multiple devices on a port [41-17](#)
 - unicast traffic [41-16](#)
 - usage guidelines [41-16](#)
- traceroute command [41-18](#)
 - See also IP traceroute
- traffic
 - blocking flooded [25-7](#)
 - fragmented [32-5](#)
 - unfragmented [32-5](#)
- traffic policing [1-9](#)
- traffic suppression [25-1](#)
- transparent mode, VTP [14-3, 14-12](#)
- trap-door mechanism [3-2](#)
- traps
 - configuring MAC address notification [7-22](#)
 - configuring managers [31-11](#)
 - defined [31-3](#)
 - enabling [7-22, 31-11](#)
 - notification types [31-11](#)
 - overview [31-1, 31-4](#)
- troubleshooting
 - connectivity problems [41-14, 41-16, 41-17](#)
 - detecting unidirectional links [27-1](#)
 - displaying crash information [41-24](#)
 - PIMv1 and PIMv2 interoperability problems [38-23](#)
 - setting packet forwarding [41-22](#)
 - SFP security and identification [41-13](#)

- troubleshooting (continued)
 - show forward command [41-22](#)
 - with CiscoWorks [31-4](#)
 - with debug commands [41-20](#)
 - with ping [41-14](#)
 - with system message logging [31-1](#)
 - with traceroute [41-17](#)
 - trunking encapsulation [1-7](#)
 - trunk ports
 - configuring [13-21](#)
 - defined [11-3, 13-3](#)
 - encapsulation [13-21, 13-26, 13-27](#)
 - trunks
 - allowed-VLAN list [13-22](#)
 - configuring [13-21, 13-26, 13-27](#)
 - ISL [13-16](#)
 - load sharing
 - setting STP path costs [13-26](#)
 - using STP port priorities [13-24, 13-25](#)
 - native VLAN for untagged traffic [13-23](#)
 - parallel [13-26](#)
 - pruning-eligible list [13-23](#)
 - to non-DTP device [13-17](#)
 - trusted boundary for QoS [33-38](#)
 - trusted port states
 - between QoS domains [33-40](#)
 - classification options [33-5](#)
 - ensuring port security for IP phones [33-38](#)
 - support for [1-9](#)
 - within a QoS domain [33-36](#)
 - trustpoints, CA [9-42](#)
 - tunneling
 - defined [17-1](#)
 - IEEE 802.1Q [17-1](#)
 - Layer 2 protocol [17-8](#)
 - tunnel ports
 - defined [13-4](#)
 - described [11-4, 17-1](#)
 - tunnel ports (continued)
 - IEEE 802.1Q, configuring [17-6](#)
 - incompatibilities with other features [17-6](#)
 - twisted-pair Ethernet, detecting unidirectional links [27-1](#)
 - type of service
 - See ToS
-
- ## U
- UDLD
 - configuration guidelines [27-4](#)
 - default configuration [27-4](#)
 - disabling
 - globally [27-5](#)
 - on fiber-optic interfaces [27-5](#)
 - per interface [27-6](#)
 - echoing detection mechanism [27-3](#)
 - enabling
 - globally [27-5](#)
 - per interface [27-6](#)
 - Layer 2 protocol tunneling [17-10](#)
 - link-detection mechanism [27-1](#)
 - neighbor database [27-2](#)
 - overview [27-1](#)
 - resetting an interface [27-6](#)
 - status, displaying [27-7](#)
 - support for [1-6](#)
 - UDP, configuring [35-16](#)
 - unauthorized ports with IEEE 802.1x [10-4](#)
 - unicast MAC address filtering [1-5](#)
 - and adding static addresses [7-25](#)
 - and broadcast MAC addresses [7-25](#)
 - and CPU packets [7-25](#)
 - and multicast addresses [7-25](#)
 - and router MAC addresses [7-25](#)
 - configuration guidelines [7-25](#)
 - described [7-25](#)
 - unicast storm [25-1](#)
 - unicast storm control command [25-4](#)

unicast traffic, blocking [25-7](#)

UniDirectional Link Detection protocol

See UDLD

UNIX syslog servers

daemon configuration [31-12](#)

facilities supported [31-13](#)

message logging configuration [31-12](#)

unrecognized Type-Length-Value (TLV) support [14-4](#)

upgrading information

See release notes

upgrading software images

See downloading

UplinkFast

described [20-4](#)

disabling [20-16](#)

enabling [20-15](#)

support for [1-6](#)

uploading

configuration files

preparing [B-11](#), [B-13](#), [B-16](#)

reasons for [B-9](#)

using FTP [B-14](#)

using RCP [B-18](#)

using TFTP [B-12](#)

image files

preparing [B-21](#), [B-25](#), [B-29](#)

reasons for [B-19](#)

using FTP [B-28](#)

using RCP [B-33](#)

using TFTP [B-24](#)

User Datagram Protocol

See UDP

user EXEC mode [2-2](#)

username-based authentication [9-6](#)

V

version-dependent transparent mode [14-4](#)

version-mismatch (VM) mode

automatic upgrades with auto-upgrade [5-11](#)

described [5-10](#)

displaying [5-11](#)

manual upgrades with auto-advise [5-11](#)

Virtual Private Network

See VPN

virtual router [37-1](#), [37-2](#)

vlan.dat file [13-5](#)

VLAN 1, disabling on a trunk port [13-22](#)

VLAN 1 minimization [13-22](#)

VLAN ACLs

See VLAN maps

vlan-assignment response, VMPS [13-28](#)

VLAN configuration

at bootup [13-7](#)

saving [13-7](#)

VLAN configuration mode [2-2](#), [13-7](#)

VLAN database

and startup configuration file [13-7](#)

and VTP [14-1](#)

VLAN configuration saved in [13-7](#)

VLANs saved in [13-4](#)

vlan database command [13-7](#)

vlan dot1q tag native command [17-5](#)

VLAN filtering and SPAN [28-7](#)

vlan global configuration command [13-7](#)

VLAN ID, discovering [7-27](#)

VLAN management domain [14-2](#)

VLAN Management Policy Server

See VMPS

VLAN map entries, order of [32-30](#)

- VLAN maps
 - applying [32-34](#)
 - common uses for [32-34](#)
 - configuration guidelines [32-30](#)
 - configuring [32-30](#)
 - creating [32-31](#)
 - defined [32-2](#)
 - denying access to a server example [32-36](#)
 - denying and permitting packets [32-32](#)
 - displaying [32-41](#)
 - examples of ACLs and VLAN maps [32-32](#)
 - removing [32-34](#)
 - support for [1-7](#)
 - wiring closet configuration example [32-35](#)
- VLAN membership
 - confirming [13-31](#)
 - modes [13-3](#)
- VLAN Query Protocol
 - See VQP
- VLANs
 - adding [13-8](#)
 - adding to VLAN database [13-8](#)
 - aging dynamic addresses [18-9](#)
 - allowed on trunk [13-22](#)
 - and spanning-tree instances [13-3, 13-6, 13-13](#)
 - configuration guidelines, extended-range VLANs [13-12](#)
 - configuration guidelines, normal-range VLANs [13-6](#)
 - configuration options [13-7](#)
 - configuring [13-1](#)
 - configuring IDs 1006 to 4094 [13-12](#)
 - connecting through SVIs [11-9](#)
 - creating in config-vlan mode [13-9](#)
 - creating in VLAN configuration mode [13-10](#)
 - customer numbering in service-provider networks [17-3](#)
 - default configuration [13-8](#)
 - deleting [13-10](#)
 - described [11-2, 13-1](#)
 - displaying [13-15](#)
 - extended-range [13-1, 13-12](#)
- VLANs (continued)
 - features [1-7](#)
 - illustrated [13-2](#)
 - internal [13-13](#)
 - in the switch stack [13-6](#)
 - limiting source traffic with RSPAN [28-23](#)
 - limiting source traffic with SPAN [28-16](#)
 - modifying [13-8](#)
 - multicast [24-15](#)
 - native, configuring [13-23](#)
 - normal-range [13-1, 13-4](#)
 - number supported [1-7](#)
 - parameters [13-5](#)
 - port membership modes [13-3](#)
 - static-access ports [13-11](#)
 - STP and IEEE 802.1Q trunks [18-11](#)
 - supported [13-2](#)
 - Token Ring [13-6](#)
 - traffic between [13-2](#)
 - VLAN-bridge STP [18-11, 40-2](#)
 - VTP modes [14-3](#)
- VLAN Trunking Protocol
 - See VTP
- VLAN trunks [13-16](#)
- VMPS
 - administering [13-32](#)
 - configuration example [13-33](#)
 - configuration guidelines [13-29](#)
 - default configuration [13-29](#)
 - description [13-28](#)
 - dynamic port membership
 - described [13-29](#)
 - reconfirming [13-31](#)
 - troubleshooting [13-33](#)
 - entering server address [13-30](#)
 - mapping MAC addresses to VLANs [13-28](#)
 - monitoring [13-32](#)

VMPS (continued)

- reconfirmation interval, changing [13-31](#)
- reconfirming membership [13-31](#)
- retry count, changing [13-32](#)

voice-over-IP [15-1](#)

voice VLAN

- Cisco 7960 phone, port connections [15-1](#)
- configuration guidelines [15-3](#)
- configuring IP phones for data traffic
 - override CoS of incoming frame [15-6](#)
 - trust CoS priority of incoming frame [15-6](#)
- configuring ports for voice traffic in
 - 802.1p priority tagged frames [15-5](#)
 - 802.1Q frames [15-5](#)
- connecting to an IP phone [15-4](#)
- default configuration [15-3](#)
- described [15-1](#)
- displaying [15-6](#)
- IP phone data traffic, described [15-2](#)
- IP phone voice traffic, described [15-2](#)

VPN

- configuring routing in [35-67](#)
- forwarding [35-65](#)
- in service provider networks [35-63](#)
- routes [35-64](#)

VPN routing and forwarding table

See VRF

VQP [1-7, 13-28](#)

VRF

- defining [35-65](#)
- tables [35-63](#)

VTP

- adding a client to a domain [14-14](#)
- advertisements [13-19, 14-3](#)
- and extended-range VLANs [14-2](#)
- and normal-range VLANs [14-2](#)
- client mode, configuring [14-11](#)

VTP (continued)

configuration

- global configuration mode [14-7](#)
- guidelines [14-8](#)
- privileged EXEC mode [14-7](#)
- requirements [14-9](#)
- saving [14-7](#)
- VLAN configuration mode [14-8](#)

configuration mode options [14-7](#)configuration requirements [14-9](#)

configuration revision number

- guideline [14-14](#)
- resetting [14-15](#)

configuring

- client mode [14-11](#)
- server mode [14-9](#)
- transparent mode [14-12](#)

consistency checks [14-4](#)default configuration [14-7](#)described [14-1](#)disabling [14-12](#)domain names [14-8](#)domains [14-2](#)Layer 2 protocol tunneling [17-8](#)

modes

- client [14-3, 14-11](#)
- server [14-3, 14-9](#)
- transitions [14-3](#)
- transparent [14-3, 14-12](#)

monitoring [14-16](#)passwords [14-8](#)

pruning

- disabling [14-14](#)
- enabling [14-14](#)
- examples [14-5](#)
- overview [14-4](#)
- support for [1-7](#)

pruning-eligible list, changing [13-23](#)server mode, configuring [14-9](#)

VTP (continued)

- statistics [14-16](#)
- support for [1-7](#)
- Token Ring support [14-4](#)
- transparent mode, configuring [14-12](#)
 - using [14-1](#)
- version, guidelines [14-9](#)
- Version 1 [14-4](#)
- Version 2
 - configuration guidelines [14-9](#)
 - disabling [14-13](#)
 - enabling [14-13](#)
 - overview [14-4](#)

W

weighted tail drop

See WTD

wizards [1-2](#)

WTD

- described [33-13](#)
- setting thresholds
 - egress queue-sets [33-72](#)
 - ingress queues [33-68](#)
- support for [1-9](#)

X

Xmodem protocol [41-2](#)

