

## Cisco CRS-3 1-Port 100 Gigabit Ethernet Interface Module

The Cisco® CRS-3 Carrier Routing System offers industry-leading performance, advanced services intelligence, environmentally conscious design, and system longevity. The Cisco CRS-3 is powered by the Cisco QuantumFlow Array – a chipset architecture based on multidimensional engineering and Cisco IOS® XR Software, a unique self-healing, distributed operating system.

Packet-based data communications are being replaced by video and rich media traversing the IP Next-Generation Network (NGN) in multiple directions, straining the architectural foundations of both public and private networks serving businesses and consumers. As part of the medianet, a media-aware Cisco IP NGN, the Cisco CRS-3 delivers continuous, always-on operations and scales easily from numerous single-chassis form factors to a massive multi-chassis system. Its design provides an industry-leading efficiency consuming lowest power, cooling and rack-space resources for an intelligent service-rich bandwidth capacity. The CRS-3 builds on the CRS-1 being backward and forward compatible, protecting existing and future investments for decades to come.

This data sheet provides detailed product specifications for the Cisco CRS-3 1-Port 100 Gigabit Ethernet Interface Module (product number 1X100GBE). For more information about the Cisco CRS Family or about other available interfaces, visit: <http://www.cisco.com/go/crs>.

**Figure 1.** Cisco CRS-3 1-Port 100 Gigabit Ethernet Interface Module



## Product Specifications

Table 1 gives specifications of the Cisco CRS-3 1 port 100 Gigabit Ethernet Interface Module.

**Table 1.** Product Specifications

Feature	Description
<b>Chassis compatibility</b>	<ul style="list-style-type: none"> <li>Compatible with all current Cisco CRS-3 line-card chassis</li> <li>Compatible with all current Cisco CRS-1 line-card chassis with 140G fabric cards</li> <li>Requires Cisco 140G Modular Services Card or 140G Forwarding Processor Card for operation</li> </ul>
<b>Software compatibility</b>	Cisco IOS XR Software Release 4.0.0 or later
<b>Port density</b>	One port of 100 Gigabit Ethernet per PLIM slot
<b>Ethernet</b>	<ul style="list-style-type: none"> <li>IEEE 802.3ba compliant</li> <li>100GE PHY Monitoring</li> <li>Encapsulations: ARPA, IEEE 802.2/SAP, IEEE 802.3/SNAP</li> <li>IEEE 802.x flow control</li> <li>802.1q VLAN support, jumbo frames</li> <li>IEEE 802.1p tagging</li> <li>Source/destination MAC accounting and VLAN accounting</li> <li>Full-duplex operation</li> <li>802.1Q VLAN termination</li> <li>Per-port byte and packet counters for policy drops; oversubscription drops; cyclic redundancy check (CRC) error drops; packet sizes; and unicast, multicast, and broadcast packets</li> <li>Per-VLAN byte and packet counters for policy drops; oversubscription drops; and unicast, multicast, and broadcast packets</li> <li>Per-port byte counters for good bytes and dropped bytes</li> </ul>
<b>Performance</b>	<ul style="list-style-type: none"> <li>100-Gbps line-rate throughput</li> <li>Maximum number of IM per chassis: 4 slot (4), 8 slot (8), 16 slot (16)</li> </ul>
<b>Reliability and availability</b>	<ul style="list-style-type: none"> <li>Line-card online insertion and removal (OIR) support without system impact.</li> </ul>
<b>Network management</b>	<ul style="list-style-type: none"> <li>Cisco IOS XR Software command-line interface (CLI)</li> <li>Simple Network Management Protocol (SNMP)</li> <li>Extensible Markup Language (XML) interface</li> <li>CraftWorks Interface (CWI)</li> <li>Cisco Active Network Abstraction (ANA)</li> </ul>
<b>Physical dimensions</b>	<ul style="list-style-type: none"> <li>Occupies one-half slot on a Cisco CRS-3 and CRS-1 chassis</li> <li>Weight: 7.17 lbs (3.24 kg)</li> <li>Height: 20.6 in. (52.2 cm)</li> <li>Depth: 11.2 in. (28.4 cm)</li> <li>Width: 1.8 in. (4.49 cm)</li> </ul>
<b>Power</b>	150 Watts
<b>Environmental conditions</b>	<ul style="list-style-type: none"> <li>Storage temperature: -40 to 70°C (-40 to 158°F)</li> <li>Operating temperature: <ul style="list-style-type: none"> <li>Normal: 5 to 40°C (41 to 104°F)</li> <li>Short-term: -5 to 50°C (23 to 122°F)</li> </ul> </li> <li>Relative humidity: <ul style="list-style-type: none"> <li>Normal: 5 to 85%</li> <li>Short-term: 5 to 90% but not to exceed 0.024 kg water/kg of dry air</li> </ul> </li> </ul> <p>Short-term refers to a period of not more than 96 consecutive hours and a total of not more than 15 days in 1 year. (This refers to a total of 360 hours in any given year, but no more than 15 occurrences during that 1-year period.)</p>

## Approvals and Compliance

Table 2 gives standards compliance information for the Cisco CRS-3 1-Port 100 Gigabit Ethernet Interface Module.

**Table 2.** Compliance and Agency Approvals

Feature	Description
<b>Safety Standards</b>	<ul style="list-style-type: none"> <li>UL/CSA/IEC/EN 60950-1</li> <li>AS/NZS 60950.1</li> <li>IEC/EN 60825 Laser Safety</li> <li>FDA—Code of Federal Regulations Laser Safety</li> </ul>
<b>EMI</b>	<ul style="list-style-type: none"> <li>FCC Class A</li> <li>ICES 003 Class A</li> <li>AS/NZS CISPR 22 Class A</li> <li>CISPR 22 (EN55022) Class A</li> <li>VCCI Class A</li> <li>IEC/EN 61000-3-2: Power Line Harmonics</li> <li>IEC/EN 61000-3-3: Voltage Fluctuations and Flicker</li> </ul>
<b>Immunity (Basic Standards)</b>	<ul style="list-style-type: none"> <li>IEC/EN-61000-4-2: Electrostatic Discharge Immunity (8-kV contact, 15-kV air)</li> <li>IEC/EN-61000-4-3: Radiated Immunity (10V/m)</li> <li>IEC/EN-61000-4-4: Electrical Fast Transient Immunity (2-kV power, 1-kV signal)</li> <li>IEC/EN-61000-4-5: Surge AC Port (4-kV CM, 2-kV DM)</li> <li>IEC/EN-61000-4-5: Signal Ports (1 kV)</li> <li>IEC/EN-61000-4-5: Surge DC Port (1 kV)</li> <li>IEC/EN-61000-4-6: Immunity to Conducted Disturbances (10 Vrms)</li> <li>IEC/EN-61000-4-8: Power Frequency Magnetic Field Immunity (30A/m)</li> <li>IEC/EN-61000-4-11: Voltage Dips, Short Interruptions, and Voltage Variations</li> </ul>
<b>ETSI and EN</b>	<ul style="list-style-type: none"> <li>EN300 386: Telecommunications Network Equipment (EMC)</li> <li>EN55022: Information Technology Equipment (Emissions)</li> <li>EN55024: Information Technology Equipment (Immunity)</li> <li>EN50082-1/EN-61000-6-1: Generic Immunity Standard</li> </ul>
<b>Network Equipment Building Standards (NEBS)</b>	<p>This product is designed to meet the following requirements (qualification in progress):</p> <ul style="list-style-type: none"> <li>SR-3580: NEBS Criteria Levels (Level 3)</li> <li>GR-1089-CORE: NEBS EMC and Safety</li> <li>GR-63-CORE: NEBS Physical Protection</li> </ul>

## Additional Specifications

**Table 3.** Additional Specifications

100 Gigabit Ethernet CFP Optics	Maximum Distance
100 Gigabit Ethernet long-reach over 4 WDM Lanes (LR4) Optics (single-mode fiber)	6.2 mi (10 km)

## Ordering Information

To place an order, contact your local Cisco representative or visit the Cisco Ordering Home Page. Use the ordering information in Table 4.

**Table 4.** Ordering Information

Product Part Number	Product Name
1X100GBE	Cisco CRS-3 1-port 100 Gigabit Ethernet Interface Module
CFP-100G-LR4	Cisco 100 Gigabit Ethernet LR4 (10 km) Optics

## Cisco Services

Cisco Services make networks, applications, and the people who use them work better together.

Today, the network is a strategic platform in a world that demands better integration between people, information, and ideas. The network works better when services, together with products, create solutions aligned with business needs and opportunities.

The unique Cisco Lifecycle approach to services defines the requisite activities at each phase of the network lifecycle to help ensure service excellence. With a collaborative delivery methodology that joins the forces of Cisco, our skilled network of partners, and our customers, we achieve the best results.

## For More Information

For more information about the Cisco CRS-3 1-Port 100 Gigabit Ethernet Interface Module, contact your local Cisco representative or visit: <http://www.cisco.com/go/crs>.



**Americas Headquarters**  
Cisco Systems, Inc.  
San Jose, CA

**Asia Pacific Headquarters**  
Cisco Systems (USA) Pte. Ltd.  
Singapore

**Europe Headquarters**  
Cisco Systems International BV  
Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).

CCDE, CCENT, CCSI, Cisco Eos, Cisco Explorer, Cisco HealthPresence, Cisco IronPort, the Cisco logo, Cisco Nurse Connect, Cisco Pulse, Cisco SensorBase, Cisco StackPower, Cisco StadiumVision, Cisco TelePresence, Cisco TrustSec, Cisco Unified Computing System, Cisco WebEx, DCE, Flip Channels, Flip for Good, Flip Mino, Flipshare (Design), Flip Ultra, Flip Video, Flip Video (Design), Instant Broadband, and Welcome to the Human Network are trademarks; Changing the Way We Work, Live, Play, and Learn, Cisco Capital, Cisco Capital (Design), CiscoFinanced (Stylized), Cisco Store, Flip Gift Card, and One Million Acts of Green are service marks; and Access Registrar, Aironet, AllTouch, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, CCVP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Lumin, Cisco Nexus, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, Continuum, EtherFast, EtherSwitch, Event Center, Explorer, Follow Me Browsing, GainMaker, iLYNX, IOS, iPhone, IronPort, the IronPort logo, Laser Link, LightStream, Linksys, MeetingPlace, MeetingPlace Chime Sound, MGX, Networkers, Networking Academy, PCNow, PIX, PowerKEY, PowerPanels, PowerTV, PowerTV (Design), PowerVu, Prisma, ProConnect, ROSA, SenderBase, SMARTnet, Spectrum Expert, StackWise, WebEx, and the WebEx logo are registered trademarks of Cisco and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1002R)